



Matching SLIM series pendant lamps are available for the current track system. The die-cast aluminium light body is the same size for all variants [300 × 39 mm]. The pendant lamps for current tracks allow suspended mounting up to 1,800 mm.

The single-luminaire SLIM current track light is therefore ideal for gastronomy and retail projects with changing room layouts. The premium SLIM series is rounded off with a flexible fabric cable.

Special features

- Extra-soft fabric cable
- Glare-free, due to low UGR value [<19]
- Slim design at just 39 mm in diameter
- Max. suspended mounting: 1,800 mm

Housing Material	Aluminium
Housing Color	Black
Colour of Lens	Transparent
Surface Structure of Lens	Structured
Halogen free	No
Protection Class	Protection class I/protective grounding
Rated Input	5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Diameter	39 mm
Product weight	433 g
Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 65 °C
IP Protection Class	IP 20

Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	5 kWh/1000h
Energy Efficiency Class Lightsources	This product contains a light source of energy efficiency class E.

Light Source	LED, Light source changeable TC
Lightcolor	Warm white (WW)
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	500 lm
Luminous Efficiency	100 lm/W
Rated Angle of Reflection	24 Degree
UGR	19
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	1800 mm
Height	300 mm

