




Our LUCEA series spotlights are also available for the single-phase 230 V current track system. The ceiling light version is available in 6, 10, 15 and 20 W for a light output of up to 3,000 lumens.

Special features

- incl. black reflector ring
- Can be customised with a wide range of accessories

Housing Material	Aluminium
Housing Color	White
Material of Lens	PMMA
Halogen free	No
Protection Class	Protection class I/protective grounding
Rated Input	6 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Light Source	LED, Light source changeable TC
Lightcolor	Warm white (WW)
Color Temperature	2700 K
Colour Consistency	5 SDCM
Colour consistency light source	5 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	800 lm
Luminous Efficiency	133.3 lm/W
Rated Angle of Reflection	36 Degree

Swivel Angle	90 Degree
Rotation Angle	350 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	157 mm
Diameter	65 mm
Product weight	434 g

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 65 °C
IP Protection Class	IP 20
IK Protection Class	IK03

Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	6 kWh/1000h
Energy Efficiency Class Lightsources	This product contains a light source of energy efficiency class E.

