



Despite the linear design, the Wallwasher - CAPH series assortment is well-rounded. Wallwashers offer a variety of options for accentuating different objects, whether that's a rustic stone wall in warm 3,000 K or a modern new build in RGBW. The different visual designs with symmetrical or asymmetrical diffusion angles help with positioning.

With the 230 V variants, no further accessories are required. Thanks to the 24 V versions, the CAPH Wallwashers can be connected to all variants of the control unit on the market.

Housing Material	Aluminium	Length	1000 mm
Housing Color	Dark grey	Width	53.36 mm
Material of Lens	Glass	Height	81.07 mm
Protection Class	Protection class III/safety extra-low voltage	Working Temperature	-20 to 60 °C
Operating Mode	Constant voltage	Storage Temperature	-20 to 60 °C
Rated Input	60 W	IP Protection Class	IP 65
Rated Power Consumption Standby	0.5 W	Life Time L70 / B50	30000 h
Rated Input Voltage	24 V/DC	Switching Cycles	100000
Power Supply Unit incl.	No	Power Consumption	66 kWh/1000h
Connection Cable Primary	Yes	EEI	G
Primary Connection	WEIPU plug 5-pole		
Primary Cable Length	0.5 m		
Connection Cable Secondary	Yes		
Secondary Connection	WEIPU socket 5-pole		
Secondary Cable Length	0.5 m		
Dimmable	Yes		
Control	Dimmable via optional controller		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	2480 lm		
Rated Angle of Reflection	40 Degree		
Rated Angle of Reflection 2	15 Degree		
Light Distribution	Asymmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		