



Despite the linear design, the Wallwasher - CAPH series assortment is well-rounded. Wallwashers offer a variety of options for accentuating different objects, whether that's a rustic stone wall in warm 3,000 K or a modern new build in RGBW. The different visual designs with symmetrical or asymmetrical diffusion angles help with positioning.

With the 230 V variants, no further accessories are required. Thanks to the 24 V versions, the CAPH Wallwashers can be connected to all variants of the control unit on the market.

Housing Material	Aluminium
Housing Color	Dark grey
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	38 W
Rated Input Voltage	220-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Power plug IP44
Primary Cable Length	2 m
Connection Type According to Standard	Typ Y
Dimmable	No
Motion Detector	No
Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour consistency light source	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	3000 lm
Rated Angle of Reflection	25 Degree
Light Distribution	Symmetric
Distribution Characteristic	DLS
120°	
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top
Length	1000 mm
Width	53.36 mm
Height	81.07 mm

Special features

- Including 2 m connecting cable with IP44 shaped plug

Working Temperature	-20 to 60 °C
Storage Temperature	-20 to 60 °C
IP Protection Class Lamp	IP 65
IP Protection Class Plug	IP 44
Life Time L70 / B50	30000 h
Switching Cycles	100000
Power Consumption	38 kWh/1000h
EEI	G

