



Despite the linear design, the Wallwasher - CAPH series assortment is well-rounded. Wallwashers offer a variety of options for accentuating different objects, whether that's a rustic stone wall in warm 3,000 K or a modern new build in RGBW. The different visual designs with symmetrical or asymmetrical diffusion angles help with positioning.

With the 230 V variants, no further accessories are required. Thanks to the 24 V versions, the CAPH Wallwashers can be connected to all variants of the control unit on the market.

Housing Material	Aluminium	Height	81.07 mm
Housing Color	Dark grey	Working Temperature	-20 to 60 °C
Material of Lens	Glass	Storage Temperature	-20 to 60 °C
Protection Class	Protection class I/protective grounding	IP Protection Class Lamp	IP 65
Rated Input	38 W	IP Protection Class Plug	IP 44
Rated Input Voltage	220-240 V/AC 50 / 60 Hz	Life Time L70 / B50	30000 h
Frequency		Switching Cycles	100000
Power Supply Unit incl.	Yes	Power Consumption	38 kWh/1000h
Connection Cable Primary	Yes	EEI	G
Primary Connection	Power plug IP44		
Primary Cable Length	2 m		
Connection Type According to Standard	Typ Y		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	2580 lm		
Rated Angle of Reflection	40 Degree		
Rated Angle of Reflection 2	15 Degree		
Light Distribution	Asymmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		
Length	1000 mm		
Width	53.36 mm		

