



The new COLT series is a genuine all-rounder outdoors: Powerful, freely rotatable and tiltable and equipped with the latest LED technology, the surface-mounted lamps deliver atmospheric illumination concepts in any outdoor application and cut a fine figure even when switched off thanks to their striking design.

#### Special features

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Grey
<b>Material of Lens</b>	Glass
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	14 W
<b>Rated Power Consumption Standby</b>	0.5 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Dimmable</b>	Yes
<b>Control</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No
<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour consistency light source</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	1090 lm
<b>Rated Angle of Reflection</b>	40 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	DLS
<b>Swivel Angle</b>	180 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top
<b>Length</b>	88 mm
<b>Height</b>	220 mm
<b>Diameter</b>	110 mm
<b>Base height</b>	56 mm
<b>Base diameter</b>	120 mm

<b>Working Temperature</b>	-30 to 40 °C
<b>Storage Temperature</b>	-40 to 80 °C
<b>IP Protection Class</b>	IP 65
<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	15000
<b>Power Consumption</b>	15 kWh/1000h
<b>EEI</b>	G

