



The CATA IV series not only impresses as a modern path light but also as a stand-alone lighting and design feature when creating outdoor spaces. The LEDs not only ensure full-surface illumination of paths and entrance areas but also inevitably draw attention to the striking frame construction. Available in three sizes, the CATA IV models can also be combined really well.

Housing Material	Aluminium	Working Temperature	-20 to 50 °C
Housing Color	Grey	Storage Temperature	-10 to 60 °C
Material of Lens	Plastic	IP Protection Class	IP 54
Functions	Nightsaver	Life Time L70 / B50	30000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	15000
Rated Input	4 W	Power Consumption	4 kWh/1000h
Rated Input Voltage Frequency	100-240 V/AC 50 / 60 Hz	EEL	F
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Connection box IP65		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour consistency light source	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	170 lm		
Rated Angle of Reflection	120 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	151 mm		
Width	61 mm		
Height	700 mm		
Base length	145 mm		
Base width	55 mm		
Base height	20 mm		

