

**Special features**

- Adjustable brightness and colour saturation
- 16 million available colours and adjustable colour temperature
- 18 automatic programmes pre-installed
- Program and remote control synchronisation when operating multiple RF smart components (repeater function)
- Can be controlled with RF smart wireless remote controls (2.4 GHz, range approx. 30 m, not included in the scope of delivery)
- Can be controlled with all Zigbee 3.0 compatible controllers/apps such as Amazon Echo (Alexa), Google Assistant, Tuya (relevant)

<b>Housing Material</b>	Aluminium, Plastic
<b>Housing Color</b>	Anthracite
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	25 W
<b>Rated Power Consumption Standby</b>	1.2 W
<b>Rated Power Consumption Network Standby</b>	0.5 W
<b>Rated Input Voltage</b>	100-240 V/AC 50 / 60 Hz
<b>Frequency</b>	
<b>Power Supply Unit incl.</b>	Yes
<b>Primary Cable Length</b>	1.5 m
<b>Number of Cable Entries</b>	1 PCS
<b>Dimmable</b>	Yes
<b>Control</b>	RF-Smart, ZigBee 3.0
<b>Motion Detector</b>	No

<b>Height</b>	180 mm
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-30 to 70 °C
<b>IP Protection Class Lamp</b>	IP 65
<b>IP Protection Class Plug</b>	IP 44
<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	100000
<b>Power Consumption EEI</b>	25 kWh/1000h F

<b>Light Source</b>	LED, Light source not changeable
<b>Colour Temperature</b>	2700-6500 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour consistency light source</b>	6 SDCM
<b>CRI (Ra)</b>	80
<b>Rated Luminous Flux</b>	1700 lm
<b>Rated Angle of Reflection</b>	15 Degree
<b>Distribution Characteristic 120°</b>	DLS

<b>Swivel Angle</b>	355 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Front

<b>Length</b>	170 mm
<b>Width</b>	65 mm