DATA SHEET



AL MONZA WL TR MD WH

Item number

GTIN

EL10026102

4015120026102





Product description

Colour

- Automatic light with in-built motion detector and 130° field of detection
- Complete device comprising light holder and **bubble glass**

Technical data

GENERAL

Device category	Wall light
Product information	Intense sunlight over a longer period of time can
	change the color tone.
User interface	Adjusting controller
Remote controllable	-
Conformity	CE, EAC, RoHS, WEEE
Warranty	3 years
ATTACHMENT	
Installation type	Surface mounting
Installation position	Wall
Connectable wire cross section	2.5 mm ²
Number of contacts	4
HOUSING	
Dimensions	Length 275 mm x Width 185 mm x Height/Depth 250
	mm
Weight	1162 g
Material	ABS
Protection type	IP44
Permissible ambient temperature	-25 °C+55 °C

Glow wire test in accordance with IEC 60695-2-10	650 °C
ELECTRICAL VERSION	
Control system	ON/OFF
Protection class	П
Nominal voltage	230 V ~ / 50 Hz
LIGHT	
Diffuser	transparent
Light emission	direct
Beam angle	290 °
SENSORS	
Detection angle	130° horizontally rotatable
Detection range diagonally	12 m
Detection range head-on	4 m
Field of detection	164 m ²
Recommended installation height	1.8 m
Level of brightness	5 – 1000 lx
Switch-off delay time	5 s12 min (adjustable in steps)
Push button input	√

white, similar to RAL 9010

DATA SHEET



AL MONZA WL TR MD WH


Item number GTIN

EL10026102 4015120026102


Dimension drawing


250 mm 185 mm

Light distribution




Field of detections Detection range Circuit diagram






Standard operation with optional parallel connection of automatic luminaires.

Circuit diagram Circuit diagram





 $Standard\ operation\ with\ additional\ continuous\ lighting\ function\ through\ external\ switch.$

Standard operation with the additional possibility of switching on by hand.

Detailed product description

DATA SHEET



AL MONZA WL TR MD WH

Item number

GTIN

EL10026102

4015120026102

- Automatic light with in-built motion detector and 130° field of detection
- Complete device comprising light holder and **bubble glass**
- One-hand plug-base installation
- Covered connector base with large wiring space
- Diaphragm line entrance for quick and easy installation
- Plug-in terminal for through-wiring of the protective conductor included
- Detection and range adjustment by revolving lens
- Individual areas can be masked with the covering clips provided