



Art.no. 13676-402

EAN 7316910589409



Born out of research on Double Dynamic Lighting, Notor 65 Dynamic has a clear focus on lighting for humans. With diffuse direct/indirect light combined with directional light from a spotlight mounted in the side, dynamic and natural-like lighting is created. Delta louvre shutters provide high efficiency and optimal light comfort and this, combined with the anti-glare spotlight, makes it possible to manage UGR16 and meet the maximum average luminance requirement at workplaces with monitors 3000cd/m2 at 65-90 degrees. Can be a good luminaire in your next WELL project.

Installation Single installation in wire suspension. For wire suspension installation, wire brackets are required for flexible c/c; ordered separately, see accessories.

Connection The luminaire is equipped with an insertion hole on the top for wiring.

Design Body lacquered in white (RAL9016 G40) or black (RAL 9005 G30). Indirect light is covered by an opal film that generates a broad beam and serves as a dust cover. End caps are included in the luminaire.

Louvre Delta - micro-prism louvre shutters in acrylic (PMMA).

Light distribution Direct/indirect 30/70, narrow-beam spotlight.

Dimming CLO (Constant Light Output) and DALI as standard. Phase pulse control is available with push dimming.

Organic Response - PIR sensor with presence and daylight control.

All luminaires function as master/slave with IR communication.

Accessories Installation fittings and additional components sold separately.

Miscellaneous CLO (Constant Light Output) entails that the luminaire provides the same amount of light for the duration of its specified burn time.

Diodes are touch protected.

Ra (CRI) 90 on request.

Notor 65 Dynamic Delta

Direct/indirect, DALI/Phase-pulse, Tunable White / Tunable White

DESIGN

Light distribution	Direct/indirect	Tilt, °	90
Turn, °	360	Louvre	Delta
Colour	Black		

LIGHT DATA & PERFORMANCE

Lumen output	4169	CLO function active	Yes
CLO time, h	50000	lm/W	85
Tunable White	Yes	Tunable White range, K	2700-6500
CRI	90	SDCM	3
Melanopic DER, WW/CW	0.470/1.180	Lumen maintenance 50 000 h	L100
Lumen maintenance 75 000 h	L86	Lumen maintenance 100 000 h	L82
Lumen maintenance L100 B50, h	50000	LED driver, h/max failure %	100000/10
LED driver, 2 h/max failure %	100000/10	Energy class, LED module	D/E
PstLm	1.000	SVM	0.400

CONTROLS & CONNECTIVITY

Light control	DALI/Phase-pulse	Driver brand	Osram/Tridonic
DALI generation/address type	Dali-2/3xDT8	Power on last level	Yes
Corridor function	Yes	Switch control, max no.	10
AM	Yes	ZD4i Certified	False
Daylight functionality	False		

ELECTRICITY & ENCLOSURE

Rated supply voltage, V	220-240	Mains frequency, Hz	0, 50, 60
Protective class	1	IP rating	20
Start W	49	End W	52
Average W	51	Stand by W	0.65
Min. ambient temperature, °C	-25	Max. ambient temperature, °C	25
MCB B10A, pcs	5	MCB B16A	8
MCB C10A	8	MCB C16A	14
Surge protection CM, kV/kA	2	Surge protection DM, kV/kA	1
Power factor, 100 %	0.87		

DIMENSIONS

Length, mm	1346	Width, mm	65
Height, mm	190	Weight, kg	4.5

