


Art.no. 13679-555

EAN 7316910589508



Born out of research on Double Dynamic Lighting, Notor 65 Dynamic has a clear focus on lighting for humans. With diffuse direct/indirect light combined with directional light from a spotlight mounted in the side, dynamic and natural-like lighting is created. Delta louvre shutters provide high efficiency and optimal light comfort and this, combined with the anti-glare spotlight, makes it possible to manage UGR16 and meet the maximum average luminance requirement at workplaces with monitors 3000cd/m2 at 65-90 degrees. Can be a good luminaire in your next WELL project.

- Installation** Single installation in wire suspension. For wire suspension installation, wire brackets are required for flexible c/c; ordered separately, see accessories.
- Connection** The luminaire is equipped with an insertion hole on the top for wiring.
- Design** Body lacquered in white (RAL9016 G40) or black (RAL 9005 G30). Indirect light is covered by an opal film that generates a broad beam and serves as a dust cover. End caps are included in the luminaire.
- Louvre** Delta - micro-prism louvre shutters in acrylic (PMMA).
- Light distribution** Direct/indirect 30/70, narrow-beam spotlight.
- Dimming** CLO (Constant Light Output) and DALI as standard. Phase pulse control is available with push dimming.
- Organic Response** - PIR sensor with presence and daylight control.
- All luminaires function as master/slave with IR communication.
- Accessories** Installation fittings and additional components sold separately.
- Miscellaneous** CLO (Constant Light Output) entails that the luminaire provides the same amount of light for the duration of its specified burn time.

Diodes are touch protected.
Ra (CRI) 90 on request.

Notor 65 Dynamic Delta

Direct/indirect, Phase-pulse, 840 / 930, Double Push Dim

DESIGN

| | | | |
|--------------------|-----------------|---------|-------|
| Light distribution | Direct/indirect | Tilt, ° | 90 |
| Turn, ° | 360 | Louvre | Delta |
| Colour | White | | |

LIGHT DATA & PERFORMANCE

| | | | |
|-----------------------------|-----------|-------------------------------|-----------|
| Lumen output | 4781 | CLO function active | Yes |
| CLO time, h | 50000 | lm/W | 125 |
| CCT, K | 4000 | CRI | 80 |
| SDCM | 3 | Melanopic DER | 0.600 |
| Lumen maintenance 50 000 h | L100 | Lumen maintenance 75 000 h | L86 |
| Lumen maintenance 100 000 h | L82 | Lumen maintenance L100 B50, h | 50000 |
| LED driver, h/max failure % | 100000/10 | LED driver, 2 h/max failure % | 100000/10 |
| Energy class, LED module | C/E | | |

CONTROLS & CONNECTIVITY

| | | | |
|-------------------------|-------------|------------------------|-------|
| Light control | Phase-pulse | Driver brand | Osram |
| Power on last level | Yes | Corridor function | Yes |
| Switch control, max no. | 10 | AM | Yes |
| ZD4i Certified | False | Daylight functionality | False |

ELECTRICITY & ENCLOSURE

| | | | |
|------------------------------|---------|------------------------------|-----------|
| Rated supply voltage, V | 220-240 | Mains frequency, Hz | 0, 50, 60 |
| Protective class | 1 | IP rating | 20 |
| Start W | 39 | End W | 42 |
| Average W | 40.5 | Stand by W | 0.45 |
| Min. ambient temperature, °C | -25 | Max. ambient temperature, °C | 25 |
| MCB B10A, pcs | 7 | MCB B16A | 13 |
| MCB C10A | 13 | MCB C16A | 22 |
| Surge protection CM, kV/kA | 2 | Surge protection DM, kV/kA | 1 |
| Power factor, 100 % | 0.82 | | |

DIMENSIONS

| | | | |
|------------|------|------------|-----|
| Length, mm | 1380 | Width, mm | 65 |
| Height, mm | 190 | Weight, kg | 4.5 |

