



Art.no. 301080



A robust bollard available in three different heights makes it possible to combine high and low light points. Verda offers a simple and flexible installation even with heavy cables and smooth onward connection.

**Installation** Luminaire for assembly on foundations. Can also be cast in-situ or mounted on ground plate. Supplied with ground plate.

**Connection** Terminal block 5x16 mm².

**Design** Body of cast aluminium with screw joints of stainless steel. Diffuser of polycarbonate (PC). The ballast and fuse insert are built into the body.

**Reflector** Enamelled aluminium.

**Standard colour** Anthracite grey (Gris 900 Sablé).

Verda bollard

DESIGN

Colour Anthracite grey

LIGHT DATA & PERFORMANCE

|                              |        |                             |           |
|------------------------------|--------|-----------------------------|-----------|
| Lumen output                 | 2533   | lm/W                        | 70        |
| Light source colour          | 830    | CCT, K                      | 3000      |
| CRI                          | 80     | SDCM                        | 3         |
| Lumen maintenance L80 B10, h | 45 000 | LED driver, h/max failure % | 100000/10 |

ELECTRICITY & ENCLOSURE

|                  |    |                |    |
|------------------|----|----------------|----|
| Protective class | 1  | IP rating      | 65 |
| IK rating        | 10 | System Wattage | 36 |

DIMENSIONS

Height, mm 600