1554 - Clessidra 5 LED direct-indirect light

Code: 420599-00

Wiring name

Power factor

Insulation class

Controllability





An outdoor wall sconce with an hourglass silhouette, characterised by high quality finishes and light output. This specially designed wall light uses direct/indirect LED technology for illuminating façades and walls. It can also be used indoors thanks to its excellent finishing appearance.



		GENERAL INFORMATION
Article	1554 - Clessidra 5 LED	direct-indirect light
Code	420599-00	
		DIMENSIONS AND WEIGHT
Length (mm)	243 mm	
Width (mm)	180 mm	
Height (mm)	224 mm	
Weight (Kg)	2.7 kg	
	EL	ECTRICAL CHARACTERISTICS AND CONTROLS
Voltage type	AC	
Min Voltage (V)	220 V	
Max Voltage (V)	240 V	
Min Frequency (Hz)	50 Hz	
Max Frequency (Hz)	60 Hz	
Frequency (Hz)	50 Hz	

CLD

≥0.9

Class I

None



1554 - Clessidra 5 LED direct-indirect light

Code: 420599-00	
145 155	175" 450 175" 155" 145"
128°	360
105°	270
105°	705
95°	96
850	95
	180
	270
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	300

		MECHANICAL CHARACTERISTICS
LED flux maintenance	50000 hr, L 70, B 50	
Luminous efficacy (lm/W)	40 lm/W	
ССТ	4000 K	
Power absorption (total) (W)	22 W	
Luminous flux (output) (lm)	880 lm	
CRI	80	
Lighting source	LED	

PHOTOMETRIC DATA





Impact resistance rating (IK)

ΙP


IK07

65

1554 - Clessidra 5 LED direct-indirect light

Code: 420599-00 MATERIALS AND COLOURS

| 180 || 243 |



Housing	in die-cast aluminium.
Diffuser	tempered glass, resistant to thermal shock and impact (UNI EN 12150-1:2001).
Coating	pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised.
Colour	Graphite
Equipment	 during installation the frame stays attached via a safety hinge mechanism that prevents it from dropping down accidentally. with wall mounting plate. gasket in eco-friendly material.

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0
Markings and tests	CE
Reference standards	EN60598-1. With degree of protection according to EN60529.
Energy Label	E

WARRANTY

After sales warranty 3 yr

	DOWNLOAD

MOUNTS
AssemblyInstructions clessidra 04-23.pdf
DESIGNS

BIM 1554 Clessidra 5.zip

TechnicalDrawing 1550i.dxf

TechnicalDrawing3D disano 1554 clessidra.3ds



