



JOGG

PENDANT/CEILING LIGHT



KEY FEATURES

- Suspended mounting
- 3 different sizes 30, 40 and 60 arm.
- Ambient lighting in 3000K or 5000K colour temperatures
- A range of dimming/control options including Fixed Output, 1-10V, DALI or Touch-Dim
- G4 LED lamps
- Galvanised Aluminium finish
- Opal 'petal' diffusers, with many finish options on request



















CALL: +44 (0) 1235 55 37 69 EMAIL: sales@optelma.co.uk ISSUE DATE: 05/01/21

The Science Park Abingdon Oxfordshire OX14 3YT

SHOWROOM

23 Bowling Green Lane Clerkenwell London EC1R 0BD

PARIS OFFICE


28 Rue Charles Baudelaire 75012 Paris France

St. Urbangasse 53 Postfach 1738 CH-4502 Solothurn Switzerland



JOGG SPECIFICATIONS

PRODUCT OPTIONS							
Dimensions (mm):	Choose From The Table Below						
Cut-out (mm):							
Lifetime:	50,000 hrs						
Mounting type:	Suspended Central						
Finish:	Galvanised Aluminium						
Emergency:							
Operating voltage:	230V						
IP Rating:	IP20						
Light source:	G4 LED bulb						
Driver:	Fixed Output, 1-10V, DALI, Touch Dim.						
Colour temperature:	3000K, 5000K						
Beam Angle:	N/A						
Diffuser:	Opal polycarbonate shades						
CRI:							
Optional Extras:							



CROSS-SECTION DIMENSIONS (MM)

■ CHOOSE A SIZE TO MATCH YOUR PROJECT

Diameter x Height (mm)	Lumens/Watt *	Weight (kg)
1000 x 2700 (30arm)	5850 lm / 60 W	4 kg
1100 x 2700 (40arm)	7800 lm / 80 W	4.9 kg
1300 x 3500 (60arm)	11700 lm / 120 W	6.8 kg

^{*} Luminaire luminous flux at 4000K.

















JOGG COMPONENTS



OPAL SHADE Polycarbonate satin finish shade.



CEILING ROSE Galvanised finish.



GALVANISED ARMS Galvanised flexible

















JOGG SPECIFICATION CODE

AAAA - BB/C/D/E - F/GGG - HHHH/I										
AAAA PRODUCT ID	BB Mounting	FINISH	D DRIVER	E DIFFUSER	F Direct Led	GGG CRI / COLOUR	HHHH DIAMETER / SIZE (mm)	 Emergency		
JG30 JG40 JG60	SC		F D 1 T	0	M	930 950	30 40 60			

'X' Custom Options - specify details alongside code

'**JG30**' Jogg 30 arm, '**JG40**' Jogg 40 arm, '**JG60'** Jogg 60 arm PRODUCT ID

MOUNTING 'SC' Suspended Central

FINISH DRIVER 'F' Fixed Output, 'D' DALI, '1' 1-10V, 'T' Touch Dim

DIFFUSER 'O' Opal

'**M**' Medium power LED DIRECT LED

CRI / COLOUR '830' Colour 3000K, '850' Colour 4000K

DIAMETER / SIZE Diameter/Size in millimetres

STANDARD

Standard fixed option products for quick and easy specification. Point source LED and Linear LED solutions, organised into Track & Spots, Downlights, Recessed, Surface, Suspended and Wall mounted solutions.

MADE-TO-MEASURE

Versatile systems and luminaires with custom specifications for project-specific lighting. Available in custom sizes and lengths, with many options including curves, corners, finishes, integrated accessories and more.

BESPOKE

Bespoke luminaires demonstrating completely custom project solutions, designed with the clients from concept to delivery. Learn about the design process and inspire your next bespoke lighting project.

















FOR MORE INFORMATION OR TO TALK ABOUT A PROJECT:

CALL: +44 (0) 1235 55 37 69 EMAIL: sales@optelma.co.uk ISSUE DATE: 05/01/21

HEAD OFFICE

The Science Park Abingdon Oxfordshire OX14 3YT

SHOWROOM

23 Bowling Green Lane Clerkenwell London EC1R 0BD

PARIS OFFICE

28 Rue Charles Baudelaire 75012 Paris France

SWISS OFFICE

St. Urbangasse 53 Postfach 1738 CH-4502 Solothurn Switzerland