

The Marram Grass

POA L I LED

POA L II LED

CE | Ⓢ | Ⓜ | EN 60598-2-3 | IP 65 | 220V – 240V / 50Hz – 60Hz



- total height: 6.00m / 10.00m
- light standards: for medium and high lighting requirements
- lamp: incl. 2 or 5 glare-free P LED modules; easy to replace
- colour temperature: 3.000K warm white or 6.000K cold white
- LED gear: electronic driver, 100.000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time
- LED life expectancy: 50.000 hours/L100 for minimum maintenance costs due to an excellent thermal management
- light control: at extra cost: dimming
- optical system: directed light (multi layer) provided by an exchangeable, sealed P LED module with special lens optics
- light distribution: asymmetrical wide beam
- luminaire body: top made of corrosion resistant cast aluminium and tapered bent pole with access door for cable junction box made of hot dip galvanised steel; powder coated
- colour: RAL or DB
- glazing: PMMA RESIST, sated, high-impact
- wiring: incl. cable until access door
- installation: with root to be set into the ground
- accessories: cable junction box, foundation – to be ordered separately
- application areas: promenades, parkways, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distributor roads, paths, cycle lanes, squares, car parks, pedestrian zones

lamp	kg	product code
POA L I LED – 6,00m P LED 29,4W/3.000K	140,0	6.111.9000.11
POA L II LED – 10,00m P LED 73,5W/3.000K	320,0	6.111.9000.12

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 04.2017

