



## Tweak Essential Office

### Freestanding luminaire

2004.7055

TWEAK2 ESS S1U1950 LED9400-840 SR IF1CSEDI EU



|                                     |                      |
|-------------------------------------|----------------------|
| <b>System power</b>                 | 68 W                 |
| <b>Light control</b>                | SensoDim®            |
| <b>Colour temperature</b>           | 4000 K neutral white |
| <b>Colour / Finish</b>              | silver               |
| <b>Luminous flux of luminaire</b>   | 9400 lm              |
| <b>Weight</b>                       | 20.36 kg             |
| <b>Colour consistency SDCM</b>      | SDCM 3               |
| <b>Unified Glare Rating (UGR)</b>   | 11                   |
| <b>C0</b>                           |                      |
| <b>Colour Rendering Index (CRI)</b> | CRI > 80             |
| <b>Unified Glare Rating (UGR)</b>   | 11                   |
| <b>C90</b>                          |                      |
| <b>Maintained luminous flux</b>     | L80 50'000 h         |

Freestanding luminaire Tweak Essential Office single head face side, with LED, system power: 68 W, standby power 0.5 W, luminous flux of luminaire 9400 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax >= 65° <= 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, 19%/81%, common dimmable and switchable, with control element (1-channel) on the rod, luminaire head 2x90°adjustable, one-piece housing in die-cast aluminium, silver, VAG E 1, thermo painted, office-suitable micropismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, with interface module/switch on the base plate, 1 integral control gear, SensoDim®, with light/movement sensor, base plate, U-shaped, 2m power supply cable with IEC 7/7 european plug,

ingress protection IP20, protection class I, glow wire test 650 °C, this product contains a light source of energy efficiency class C, and EPREL registration number: 1140598,

L = 734 mm, B = 215 mm, total height = 1950 mm

## Tweak Essential Office - Freestanding luminaire

2004.7055

TWEAK2 ESS S1U1950 LED9400-840 SR IF1CSEDI EU



### **2004.4914**

ALONE at WORK

Communication module ALONE at WORK for freestanding uplighter Tweak