



Torus

Ceiling mounted luminaire

2008.7972

TORUS CW510 LED3650-940 DID DALI



System power	36 W
Light control	DALI2
Colour temperature	4000 K neutral white
Colour / Finish	white
Luminous flux of luminaire	3650 lm
Weight	12.1 kg
Colour consistency SDCM	SDCM 3
Unified Glare Rating (UGR)	19
C0	
Colour Rendering Index (CRI)	CRI > 90
Unified Glare Rating (UGR)	19
C90	
Maintained luminous flux	L80 50'000 h

Ceiling mounted luminaire Torus with LED, system power: 36 W, standby power 1 W, luminous flux of luminaire 3650 lm, colour rendering index CRI > 90, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 0.16 A, direct-indirect light emission, 92% / 8%, light fixture in polymethyl methacrylate (PMMA), transparent, inside cone white, RAL 9016, 2 integral control gears, DALI2,

protection class I, ingress protection IP40, glow wire test 650 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1542692

Ø = 510 mm, H = 183 mm