

Torus

Ceiling mounted luminaire

2011.2914

TORUS CW510 LED3450-927 DID CAS XS2



System power	36 W
Light control	Casambi
Colour temperature	2700 K warm white
Colour / Finish	white
Luminous flux of luminaire	3450 lm
Weight	12.151 kg
Colour consistency SDCM	SDCM 3
Unified Glare Rating (UGR)	19
C0	
Colour Rendering Index (CRI)	CRI > 90
Unified Glare Rating (UGR)	19
C90	
Maintained luminous flux	L80 50'000 h

Ceiling mounted luminaire Torus with LED, system power: 36 W, standby power 1 W, luminous flux of luminaire 3450 lm, colour rendering index CRI > 90, colour temperature 2700 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 0.17 A, direct-indirect light emission, 92% / 8%, light fixture in polymethyl methacrylate (PMMA), transparent, inside cone white, RAL 9016, 2 integral control gears, Casambi,

protection class I, ingress protection IP40, glow wire test 650 °C, this product contains a light source of energy efficiency class E and EPREL registration number: 864052

Ø = 510 mm, H = 183 mm