ROSS GARDAM



OAK PENDANT

delicate luminance. Each Oak Pendant Light shade is hand crafted and defined by the grain of the oak selected. The body of the light is accentuated by the intersecting hole which defines its unique form.

The Oak pendant is available in two sizes and three finishes.

AVAILABLE FINISHES



FINISH





TECHNICAL

MATERIAL OAK HARDWOOD OR BLACKWOOD HARDWOOD

LAMPING OKP.S - 8.5W, E27, 820LM, 3000K, WARM WHITE, DIMMABLE OKP.L - 13W, E27, 1521 LM, 2700K, WARM WHITE, DIMMABLE GLOBES ARE SUPPLIED WITH AUS/NZ ORDERS ONLY

E27 LAMP HOLDER IS SUPPLIED FOR 240V REGION. E26 LAMP HOLDER IS SUPPLIED FOR 120V REGION.

LED LIFESPAN

CONTROL

DIMMING RANGE 10 - 100%. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH AN ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF

VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE CANOPY

2000 / 7" (STANDARD) OR 3M / 10" (LARGE) BLACK CLOTH CORD

AND SUSPENSION WIRE

EU EN 60598.1, 60598.2.1

IP20 - FOR INDOOR USE ONLY

AS/NZS 60598.1, 60598.2.1 AU/NZ

Oak is a sustainably sourced timber pendant light which emits a







15,000 HRS

PHASE CONTROL / NETWORK CONTROL DIMMABLE

THE FIXTURE.

NOTE: LONGER LENGTHS AVAILABLE UPON REQUEST

IP RATING

CERTIFICATION

US/CAN ETL/UL 1598, CSA C22.2#250.0 SKU CODES EG. OKP.S.H-OAK =

OAK STANDARD PENDANT IN NATURAL OAK HARDWOOD

OKP.S.H-XXX OAK STANDARD PENDANT OKP.L.H-XXX OAK LARGE PENDANT

NATURAL OAK HARDWOOD (H-OAK) LIMED STAINED OAK HARDWOOD (H-LIM) BLACK STAINED OAK HARDWOOD (H-BLK)

DIMENSIONS

STANDARD - Ø215 X 260MM / Ø 8.5 X 10.3" LARGE - Ø352 X 425MM / Ø 13.8 X 16.7"

PRODUCT 4 / 10KG 15 /33LB WEIGHT

PACKAGING

L 300 W 300 H 300 / L 11.8" W 11.8" H 11.8" DIMENSIONS L 450 W 450 H 450 / L 17.7" W 17.7" H 18.5"

PACKAGING

WEIGHT

5KG / 11LB 18KG /39.7LB

DIMENSIONS







OKP.L Ø352 H425 Ø13.8" H16.7"

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE STANDARD CANOPY WILL BE SUPPLIED.

OAK STANDARD



STANDARD - 120MM SUSPENSION + FLEX CANOPY CAN.ST.120.SF.X-XXX

Ø120 X 30MM / 4.7" X 1.2"



SLIM SUSPENSION + FLEX CANOPY CAN.SL.SF.X-XXX

Ø120 X 7MM / 4.7" X 0.3"



PUCK SUSPENSION + FLEX CANOPY CAN.PK.SF.X-XXX

Ø50 X 65MM / 2" X 2.6"

OAK LARGE (EXTERNAL CEILING ANCHOR PROVIDED WITH CANOPY)



STANDARD - 120MM SINGLE PENDANT + EXTERNAL CEILING MOUNT CANOPY CAN.ST.120.SFCM.X-XXX

Ø120 X 30MM / 4.7" X 1.2"



SINGLE PENDANT + EXTERNAL CEILING MOUNT CANOPY CAN.SL.SFCM.X-XXX

Ø120 X 7MM / 4.7" X 0.3"



SINGLE PENDANT + EXTERNAL CEILING MOUNT CANOPY CAN.PK.SFCM.X-XXX

Ø50 X 65MM / 2" X 2.6"

TECHNICAL

CANOPY FINISH

MATERIAL

ANODISED ALUMINIUM / POWDERCOATED ALUMINIUM







ANODISED BLACK (A-BLK) ANODISED CLEAR (A-CHM) POWDERCOATED WHITE (C-WHT)

SKU CODES EG. CAN.ST.120.SF.A-CHM =

STANDARD SUSPENSION + FLEX CANOPY IN CHAMPAGNE ANODISED FINISH