



POLAR

WALL LIGHT

A circular motif is used throughout the Polar collection defining its minimal operative form. The Polar Wall Light utilises a unique hinge joint allowing the disc to pivot up or down, softly directing the light output. Polar’s anodised gold wall canopy provides a beautiful base for the light to mount onto the wall and houses the fully dimmable LED module.

The wall light is available in a pivot or fixed variation. The disk is available in two sizes and various painted finish options.

AVAILABLE FINISHES



TECHNICAL

MATERIAL	ANODISED ALUMINIUM AND PAINTED ALUMINIUM		SKU CODES	EG. PW.S.P-PNK= POLAR WALL LIGHT Ø300 PIVOT IN WHITE	
LAMPING	240V - 10W LED, 990LM, 3000K, WARM WHITE, DIMMABLE 120V - 13W LED, 1190LM, 2900K, WARM WHITE, DIMMABLE			PW.S.XXX	POLAR WALL LIGHT Ø300 PIVOT
LED LIFESPAN	15,000 HRS			PW.S.XXX-F	POLAR WALL LIGHT Ø300 FIXED
CONTROL	PHASE (TRAILING EDGE/LEADING EDGE) - DIMMING RANGE 5 - 100%. DIGITAL / SMART SYSTEMS (DALI/CBUS) - NON-DIMMABLE, ON/OFF FUNCTIONALITY ONLY VIA DALI SWITCH (SWITCH NOT SUPPLIED). 1-10V / 0-10V - NOT COMPATIBLE		FINISH	WHITE PAINTED (P-WHT) BLACK PAINTED (P-BLK) GREEN PAINTED (P-GRN) GOLD METALLIC PAINTED (P-GLD)	
	**FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE. .		DIMENSIONS	PW.S - Ø300 D 53 / Ø11.8" D 2.1" PW.L - Ø450 D 53 / Ø17.7" D 2.1"	
IP RATING	IP20 - FOR DRY INDOOR USE ONLY		PRODUCT WEIGHT	PW.S - 1KG / 2.2LB PW.L - 1.5KG / 3.3LB	
CERTIFICATION	AU/NZ	AS/NZS 60598.1, 60598.2.1	PACKAGING DIMENSIONS	PW.S - L 350 W 350 H 70 / L 13.8" W 13.8" H 2.8" PW.L - L 500 W 500 H 70 / L 19.7" W 19.7" H 2.8"	
	EU	EN 60598.1, 60598.2.1	PACKAGING WEIGHT	PW.S - 1KG / 2.2LB PW.L - 1.5KG / 3.3LB	
	US/CAN	ETL/UL 1598, CSA C22.2#250.0			

DIMENSIONS

