




SOLACE

PENDANT

Solace is a luminous glass tear that transforms with movement, revealing two distinct identities in light and form. Through the exploration of geometric form the interplay of two perpendicular, intersecting circles serve as the foundation for this intricate composition.

Visually enchanting, Solace emerges from a series of experiments that use innovative engineering and push the boundaries of traditional glassblowing techniques.


AVAILABLE FINISHES



TECHNICAL

MATERIAL	TREATED BRASS, GLASS		DRIVER SIZE
FINISH	ALL BRASS COMPONENTRY IS BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.		220 -240V PHASE 220-240V DALI 110-120V TRIAC 110-120V DALI
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED) 8W, 800LM, 2700K		L101 X W51 X H29 / L4" X W2" X H1.1" L145 X W30 X H21 / L5.7" X W1.2" / X H0.9" *L75 X W35 X H26.5 / L3" X W1.4" X H1" *L75 X W35 X H26.5 / L3" X W1.4" X H1"
DIMMING	220-240V REGION PHASE DIMMING RANGE 5 - 100% DALI DIMMING RANGE 1 - 100% 110-120V REGION PHASE DIMMING RANGE 3 - 100% DALI DIMMING RANGE 0.1 - 100% ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.		*DRIVER CAN BE HOUSED WITHIN STANDARD 4" OCTAGONAL JUNCTION BOX.
			SKU CODES EG. SOP.G-FCL.BR-BLK SOLACE PENDANT IN FROSTED CLEAR GLASS WITH A BLACKENED BRASS BODY SOL.G-XXX.BR-XXX GLASS FROSTED BLACK (G-FBL) FROSTED CLEAR (G-FCL) WHITE (G-WHT) BODY BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ)
LED LIFESPAN	50,000 HRS		PRODUCT WEIGHT 6KG / 13.2LB
IP RATING	IP20 - FOR INDOOR USE ONLY		PACKAGE WEIGHT 7KG / 15.5LB
CERTIFICATION	AU/NZ EU US/CAN	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 ETL/UL CERTIFICATION PENDING	PACKAGE SIZE L 360 W 360 H 550 / L 26" W 26" H 34"
CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE		

DIMENSIONS



L 195 W 195 H 690
L 7.7" W 7.7" H 51"
MIN DROP HEIGHT - H 900 / 59"

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE SLIM CANOPY WILL BE SUPPLIED.

SLIM Ø14MM FIXED CANOPY CAN.SL.F14.XX-XXX Ø120 X 7MM / 4.7" X 0.3" DRIVER HOUSED IN CEILING OR JUNCTION BOX	SLIM Ø14MM FIXED SWIVEL CANOPY CAN.SL.F14.SW.XX-XXX Ø120 X 7MM / 4.7" X 0.3" DRIVER HOUSED IN CEILING OR JUNCTION BOX	PUCK Ø14MM FIXED CANOPY CAN.PK.F14.XX-XXX Ø50 X 65MM / 2" X 2.6" DRIVER HOUSED IN CEILING	PUCK Ø14MM FIXED SWIVEL CANOPY CAN.PK.F14.SW.XX-XXX Ø50 X 65MM / 2" X 2.6" DRIVER HOUSED IN CEILING
LARGE Ø14MM FIXED CANOPY CAN.ST.170.F14.XX-XXX Ø170 X 40MM / 6.7" X 1.6" DRIVER HOUSED IN CANOPY	LARGE Ø14MM FIXED SWIVEL CANOPY CAN.ST.170.F14.SW.XX-XXX Ø170 X 40MM / 6.7" X 1.6" DRIVER HOUSED IN CANOPY		

*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION.
*POWER ACCESS POINT REQUIRED AT CENTRE OF CEILING CANOPY.