



VOLANT 21 & 32

CHANDELIER

Volant is a modern chandelier that’s almost akin to a kinetic sculpture. A static lamp with a mystifying ability to appear in motion. Solid brass bars are home to textured, tubular formed glass elements, angled to give the impression of floating objects revolving around each other. The result is an elegant equilibrium that’s at once enthralling yet soothing.


AVAILABLE FINISHES




TECHNICAL

MATERIAL	TREATED BRASS, GLASS			LED LIFESPAN	50,000 HRS			
FINISH	ALL BRASS FRAMES ARE BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.			IP RATING	IP20 - FOR INDOOR USE ONLY			
				CERTIFICATION	AU/NZ EU US/CAN	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 ETL/UL 1598, CSA C22.2#250.0		
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED)			CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE			
	VC211 - 4.4W, 610-670 LM, 2700K							
	VC212 - 8.8W, 1220-1340 LM, 2700K							
DIMMING OPTIONS	VC323 - 13.2W, 1710-2100 LM, 2700K			SKU CODES	EG. VC323.G-FLU.BR-BRZ VOLANT 323 CHANDELIER IN FLUTED CLEAR GLASS WITH A BRONZED BRASS FRAME			
	VC324 - 16W, 2060-2360 LM, 2700K							
	WATTAGE AND LUMEN OUTPUT WILL VARY SLIGHTLY DEPENDING ON CONSTANT CURRENT OUTPUT.							
	220-240V REGION							
	PHASE - DIMMING RANGE 5 - 100%							
	DALI - DIMMING RANGE 1 - 100%				VC211.G-XXX.BR-XXX	VOLANT 211 CHANDELIER		
	110-120V REGION			FINISHES GLASS	FROSTED BLACK (G-FBL) FLUTED (G-FLU) FROSTED FLUTED (G-FFL)			
	PHASE - DIMMING RANGE 3 - 100%							
	DALI - DIMMING RANGE 0.1 - 100%							
DRIVER SIZE	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.			FRAME	BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ)			
	FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.			PRODUCT WEIGHT	VC211 - 8.5KG / 19LB VC323 - 16.5KG / 36LB	VC212 - 9.5KG / 21LB VC324 - 17.5KG / 38LB		
	220 -240V			PACKAGING WEIGHT	VC211 VC212 VC323	1 X 10.5KG / 23LB, 1 X 3KG / 6.6LB 11.5KG / 25LB, 1 X 3KG / 6.6LB 1 X 13KG / 28.5LB, 1 X 7.5KG / 16.5LB 1 X 3KG / 6.6LB		
	PHASE / TRIAC				VC324	1 X 13.5KG / 30LB, 1 X 8.5KG / 19LBV 1 X 3KG / 6.6LB		
	VC 211 & 212 - L120 X W51 X H29 / L4.7" X W2" X H1.1"							
110-120V	VC 323 & 324 - L101 X W51 X H29 / L4" X W2" X H1.1"			PACKAGING SIZE	VC211	1 X L 1920 W 370 H 190 / L 75.6" W 14.6" H 8"		
	DALI					VC212	1 X L 500 W 500 H 250 / L 19.7" W 19.7" H 10"	
	ALL VC 21 & 32 - L120 X W51 X H29 / L4.7" X W2" X H1.1"						1X L 1920 W 370 H 190 / L 75.6" W 14.6" H 8"	
	PHASE / TRIAC					VC323	1 X L 500 W 500 H 250 / L 19.7" W 19.7" H 10"	
	ALL VC 21 & 323 - L75 X W35 X H26.5 / L3" X W1.4" X H1"						2 X L 1920 W 370 H 190 / L 75.6" W 14.6" H 8"	
	VC 324 - L88 X W43 X H26.5 / L3.5" X W1.7" X H1"				VC324	1 X L 500 W 500 H 250 / L 19.7" W 19.7" H 10"		
	DALI					2 X L 1920 W 370 H 190 / L 75.6" W 15" H 8"		
	ALL VC21 & 323 - L120 X W51 X H29 / L4.7" X W2" X H1.1"					1 X L 500 W 500 H 250 / L 19.7" W 19.7" H 10"		
	VC 324 - L88 X W43 X H26.5 / L3.5" X W1.7" X H1"							


DIMENSIONS




VC211  
L 1790 W 70 H 100  
L 70.5" W 3" H 4"  
MIN DROP HEIGHT - H 300 / 11.8"



VC212  
L 1790 W 70 H 100  
L 70.5" W 3" H 4"  
MIN DROP HEIGHT - H 300 / 11.8"



VC323  
L 1790 W 1790 H 350  
L 70.5" W 70.5" H 13.8"  
MIN DROP HEIGHT - H 550 / 21.7"



VC324  
L 1790 W 1790 H 350  
L 70.5" W 70.5" H 13.8"  
MIN DROP HEIGHT - H 550 / 21.7"

\*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION.  
\*POWER ACCESS POINT REQUIRED AT CENTRE OF CEILING CANOPY.

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED THE RECTANGULAR / CIRCULAR CANOPY WILL BE SUPPLIED.

RECTANGULAR (VC211 & VC212)



RECTANGULAR  
FIXED CANOPY  
CAN.VC.REC.X-XXX  
  
420 X 170 X 37MM / 16.5" X 6.7" X 1.5"  
  
DRIVER HOUSED IN CANOPY



RECTANGULAR  
FIXED SWIVEL CANOPY  
CAN.VC.REC.SW.X-XXX  
  
VARIES PER ORDER  
  
DRIVER HOUSED IN CANOPY

CIRCULAR (VC323 & VC324)



CIRCULAR  
FIXED CANOPY  
CAN.VC.CIR.X-XXX  
  
Ø480 X 37MM / 18.9" X 1.5"  
  
DRIVER HOUSED IN CANOPY



CIRCULAR  
FIXED SWIVEL CANOPY  
CAN.VC.CIR.SW.X-XXX  
  
VARIES PER ORDER  
  
DRIVER HOUSED IN CANOPY

INDIVIDUAL CANOPY



SLIM  
Ø14MM FIXED CANOPY  
CAN.SL.F14.X-XXX  
  
Ø120 X 7MM / 4.7" X 0.3"  
  
DRIVER HOUSED IN CEILING



SLIM  
Ø14MM FIXED SWIVEL CANOPY  
CAN.SL.F14.SW.X-XXX  
  
Ø120 X 7MM / 4.7" X 0.3"  
  
DRIVER HOUSED IN CEILING



PUCK  
Ø14MM FIXED CANOPY  
CAN.PK.F14.X-XXX  
  
Ø50 X 65MM / 2" X 2.6"  
  
DRIVER HOUSED IN CEILING



PUCK  
Ø14MM FIXED SWIVEL CANOPY  
CAN.PK.F14.SW.X-XXX  
  
Ø50 X 65MM / 2" X 2.6"  
  
DRIVER HOUSED IN CEILING

TECHNICAL

MATERIAL	TREATED BRASS / POWDER COATED STEEL
	<div><div> BRUSHED BRASS</div><div> BLACKENED BRASS</div><div> BRONZED BRASS</div><div> WHITE POWDERCOATED</div></div>
CANOPY FINISH	BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ) POWDERCOATED WHITE (C-WHT) (RECTANGULAR AND CIRCULAR CANOPIES ONLY)
SKU CODES	EG. CAN.VC.REC.SW.BR-NAT = RECTANGULAR FIXED SWIVEL CANOPY IN BRUSHED BRASS FINISH