


Sombreo 230

SX 978 30-9



bracket mounted luminaire

asymmetric street

LED, 3300 lm, 4000 K, CRI > 80, electronic converter, Total power: 44 W

to be mounted on poles, luminaire housing made of gravity die casting, powder-coated, Stainless steel, screws made of stainless steel, thread with insert sleeves made of stainless steel, diffuser shape made of PMMA, clear, with satin diffuser in front of light unit,

Optical system: LED reflector unit
incl. 8m feed cable,

CE, IP65, Protection Class II

colour: Selux Graphite or special finish

Height H: 435 mm

Diameter Ø: 460 mm

Weight: 7 kg

Windpressure: 0,146 m²

Make: Selux, Type: SX 978 30-9



Modifications are possible due to the constant development and improvement of LED technology.


© Selux AG, Subject to technical modification 4.2025

Selux GmbH, Volkmarstr. 18, 12099 Berlin, T +49 30 72001-0, F -100, info@selux.com, www.selux.com

Sombreo 230

SX 978 30-9

Technics



Photometric data: 8225

Upward light ratio (ULR): 6.1 %

Lamp

LED 3300lm, 44W, 4000 K, CRI > 80

Optic

LED reflector unit · asymmetric street

Electrics

electronic converter · Total power: 44W ·

8m feed cable

control options:

dynamic · DALI · fix value · CLT · HNS ·

individual power reduction in 300 lumen

steps ex work ·

Luminous flux characteristics / Operating time of LED

	20000	40000	60000	80000
Operating time LED				
Lumen maintenance	96%	93%	90%	87%
LLMF*	0.96	0.93	0.9	0.87

* = Lamp lumen maintenance factor

Modifications are possible due to the constant development and improvement of LED technology.

© Selux AG, Subject to technical modification 4.2025

Selux GmbH, Volkmarstr. 18, 12099 Berlin, T +49 30 72001-0, F -100, info@selux.com, www.selux.com