



The Sera Technologies Suspended LED Ring Pendant is an impressive light fitting that can illuminate a large open space and create a stunning design feature. The pendant can be suspended from a central rose (supplied) or using vertical suspension cables. The fitting has a powder coated aluminium body and opal diffuser and uses energy efficient LED technology.

- Decorative suspended LED luminaire
 - Approx 110 Lumens per circuit watt
- Direct or Direct/Indirect (78:22 ratio) output options
 - DALI dimmable driver as standard
- 3-hole ceiling rose or vertical wire suspension (1.5m as standard)
 - 650mm, 950mm, 1250mm or 1550mm diameter
 - Colour Temperature = 4000K
 - CRI > 80
 - Opal polycarbonate diffuser
- White or Black finish (body and rose)
- Non-standard options also available

Technical Data

Size	Driver	CCT	Type	Height	Profile Width	Direct Output	Indirect Output	Rose	Weight
650mm	DALI	4000K	Direct	82mm	78mm	45W/4950lm	N/A	120mm	4.5 kg
650mm	DALI	4000K	Direct/Indirect	100mm	78mm	45W/4950lm	13W/1430lm	120mm	5 kg
950mm	DALI	4000K	Direct	82mm	78mm	68W/7480lm	N/A	120mm	7.5 kg
950mm	DALI	4000K	Direct/Indirect	100mm	78mm	68W/7480lm	19W/2090lm	120mm	8 kg
1250mm	DALI	4000K	Direct	82mm	78mm	90W/9900lm	N/A	200mm	12 kg
1250mm	DALI	4000K	Direct/Indirect	100mm	78mm	90W/9900lm	25W/2750lm	200mm	12.5 kg
1550mm	DALI	4000K	Direct	82mm	78mm	110W/12100lm	N/A	200mm	15 kg
1550mm	DALI	4000K	Direct/Indirect	100mm	78mm	110W/12100lm	34W/3740lm	200mm	15.5 kg

