




TIMR-PA 201.927.MF



Colours	Article no.	EAN
ash	665507	4043544794925



Description

- sustainable pendant luminaire with cylindrical ash wood housing
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management via integrated aluminium support frame (no heat sink required)
- high-tech reflector lense made from PMMA for optimum light output and glare-free lighting
- black ceiling box with feed-in made from aluminium (D = 90 mm, H = 75 mm)
- suspension with black textile cable (2 x 0.5 mm², length: 1500 mm)
- ceiling box for screw mounting
- 3-pole prefabricated connecting cable
- ballast (LED converter) integrated in ceiling box

Notes

..

Lighting data / Norms

EPREL light sources	1115627
System power	13.4 W
Luminaire luminous flux	1730 lm
System efficiency	129.10 lm/W
Module efficiency	134.07 lm/W
UGR class	≤22
Beam range	Medium Flood
Beam angle	25°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Outer diameter	102 mm
Inner diameter	75 mm
Height	132 mm
Net weight	1.09 kg
Gross weight	1.15 kg

TIMR-PA 201.927.MF

TIMR-PA 201.927.MF

Timba Round | Pendant (1xLED 13W 827/2700K 1730lm)



	C0	C90	C180	C270
0°	4249	4249	4249	4249
15°	1427	1427	1427	1427
30°	123	123	123	123
45°	36	36	36	36
60°	20	20	20	20
75°	11	11	11	11
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]	Illuminance [lx]
C0-C180 Plane		
3.0	1.35	816.7
6.0	2.70	204.2
9.0	4.04	90.7
12.0	5.39	51.0
15.0	6.74	32.7

η	LED
Efficiency	133 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	13 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	21.0
UGR C90/C270	21.0
CIE Flux Codes	93 97 99 100 100
Ra/CRI	>80

LTS