


# BOSTON/AM

7023AM2703BB

**TEC-MAR®**  
LIGHTING




## SPECIFIC PRODUCT

<b>Mod</b>	AM
<b>Color</b>	Matt white
<b>Installation</b>	Led bollard
<b>Application</b>	Outdoor
<b>Materials</b>	Die-cast aluminum body with extruded aluminum pole, painted with epoxy powders, matt white color
<b>Insulation class</b>	Class I
<b>Protection index</b>	IP66
<b>Impact degree</b>	IK08
<b>Ambient temperature (Ta)</b>	-25 / 45 °C
<b>Optics</b>	45° asymmetrical reflector in matt black painted steel sheet. Single-side lighting. Sanded extra-clear glass diffuser
<b>Beam angle</b>	45°
<b>Power supply</b>	220-240Vac
<b>Frequency</b>	50/60Hz
<b>Led modules</b>	Removable (Class: D)
<b>Standard equipment</b>	- 1000 mm long H05RN-F 3x1 mm <sup>2</sup> neoprene cable. - Anti-condensation osmotic valve.
<b>Luminous flux maintenance</b>	L80-B50 > 75.000 h L80-B20 > 50.000 h
<b>Wiring</b>	Removable
<b>Step Mac Adams</b>	3 step
<b>Photobiological safety class</b>	Risk exempt group
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1
<b>Warranty</b>	7 years

## PRODUCT FEATURES

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
3	-	2700°K - CRI>80	1500 mm	278	93	60	60	1500	-	3.2



## RELATED ACCESSORIES



### **ACC221**

IP68 T-connector for through wiring. 5-pole connection.



### **ACC241**

Universal dimmer with 230Vac phase cut output.

**TEC-MAR**  
LIGHTING

**TEC-MAR S.r.l. Via delle Industrie 1, 26835 Crespiatica (LO) – Italy**

TEC-MAR S.r.l. reserves the right, without notice, to modify the characteristics of its products as well as their availability at any time. All products, related technical data, illustrations and information are not binding for TEC-MAR S.r.l. TEC-MAR S.r.l. will not be liable for any illustrative, textual and/or translation errors. All values reported are measurement values. Flow, CCT and power data are within tolerances of +/- 10%.

29-02-2024