


# BOSTON/AM

7023AM2703BL

**TEC-MAR®**  
L I G H T I N G




## SPECIFIC PRODUCT

Mod	AM
Color	Matt white
Installation	Led bollard
Application	Outdoor
Materials	Die-cast aluminum body with extruded aluminum pole, painted with epoxy powders, matt white color
Insulation class	Class I
Protection index	IP66
Impact degree	IK08
Ambient temperature (Ta)	'-25 / 45 °C
Optics	45° asymmetrical reflector in matt black painted steel sheet. Single-side lighting. Sanded extra-clear glass diffuser
Beam angle	45°
Power supply	220-240Vac
Frequency	50/60Hz
Led modules	Removable (Class: D)
Standard equipment	<ul style="list-style-type: none"><li>- 1000 mm long H05RN-F 3x1 mm<sup>2</sup> neoprene cable.</li><li>- Anti-condensation osmotic valve.</li></ul>
Luminous flux maintenance	<ul style="list-style-type: none"><li>L80-B50 &gt; 75.000 h</li><li>L80-B20 &gt; 50.000 h</li></ul>
Wiring	Removable
Step Mac Adams	3 step
Photobiological safety class	Risk exempt group
Trademarks and certifications	CE / UNI EN 60598-1
Warranty	7 years

## PRODUCT FEATURES

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
3	-	2700°K - CRI>80	1000 mm	278	93	60	60	1000	-	2.2



RELATED ACCESSORIES



**ACC221**  
IP68 T-connector for  
through wiring. 5-pole  
connection.



**ACC241**  
Universal dimmer with  
230Vac phase cut output.