


BOSTON/AM

7023AM3003BB

TEC-MAR®
LIGHTING




SPECIFIC PRODUCT

Mod	AM
Color	Matt white
Installation	Led bollard
Application	Outdoor
Materials	Die-cast aluminum body with extruded aluminum pole, painted with epoxy powders, matt white color
Insulation class	Class I
Protection index	IP66
Impact degree	IK08
Ambient temperature (Ta)	-25 / 45 °C
Optics	45° asymmetrical reflector in matt black painted steel sheet. Single-side lighting. Sanded extra-clear glass diffuser
Beam angle	45°
Power supply	220-240Vac
Frequency	50/60Hz
Led modules	Removable (Class: D)
Standard equipment	<div>- 1000 mm long H05RN-F 3x1 mm² neoprene cable.</div> <div>- Anti-condensation osmotic valve.</div>
Luminous flux maintenance	<div>L80-B50 > 75.000 h</div> <div>L80-B20 > 50.000 h</div>
Wiring	Removable
Step Mac Adams	3 step
Photobiological safety class	Risk exempt group
Trademarks and certifications	CE / UNI EN 60598-1
Warranty	7 years

PRODUCT FEATURES

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
3	-	3000°K - CRI>80	1500 mm	287	96	60	60	1500	-	3.2



RELATED ACCESSORIES



ACC221
IP68 T-connector for
through wiring. 5-pole
connection.



ACC241
Universal dimmer with
230Vac phase cut output.