


# BOSTON/AM

7023AM3003BS

**TEC-MAR®**  
LIGHTING




## SPECIFIC PRODUCT

<b>Mod</b>	AM
<b>Color</b>	Matt white
<b>Installation</b>	Led bollard
<b>Application</b>	Outdoor
<b>Materials</b>	Die-cast aluminum body with extruded aluminum pole, painted with epoxy powders, matt white color
<b>Insulation class</b>	Class I
<b>Protection index</b>	IP66
<b>Impact degree</b>	IK08
<b>Ambient temperature (Ta)</b>	'-25 / 45 °C
<b>Optics</b>	45° asymmetrical reflector in matt black painted steel sheet. Single-side lighting. Sanded extra-clear glass diffuser
<b>Beam angle</b>	45°
<b>Power supply</b>	220-240Vac
<b>Frequency</b>	50/60Hz
<b>Led modules</b>	Removable (Class: D)
<b>Standard equipment</b>	- 1000 mm long H05RN-F 3x1 mm <sup>2</sup> neoprene cable. - Anti-condensation osmotic valve.
<b>Luminous flux maintenance</b>	L80-B50 > 75.000 h L80-B20 > 50.000 h
<b>Wiring</b>	Removable
<b>Step Mac Adams</b>	3 step
<b>Photobiological safety class</b>	Risk exempt group
<b>Trademarks and certifications</b>	CE / UNI EN 60598-1
<b>Warranty</b>	7 years

## PRODUCT FEATURES

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
3	-	3000°K - CRI>80	250 mm	287	96	60	60	250	-	0.8



## RELATED ACCESSORIES



### ACC221

IP68 T-connector for through wiring. 5-pole connection.



### ACC241

Universal dimmer with 230Vac phase cut output.

**TEC-MAR**  
LIGHTING

**TEC-MAR S.r.l. Via delle Industrie 1, 26835 Crespiatica (LO) – Italy**

TEC-MAR S.r.l. reserves the right, without notice, to modify the characteristics of its products as well as their availability at any time. All products, related technical data, illustrations and information are not binding for TEC-MAR S.r.l. TEC-MAR S.r.l. will not be liable for any illustrative, textual and/or translation errors. All values reported are measurement values. Flow, CCT and power data are within tolerances of +/- 10%.

29-02-2024