


BOSTON/AM

7023AM4004BL

TEC-MAR
LIGHTING




SPECIFIC PRODUCT

Mod	AM
Color	Matt white
Installation	Led bollard
Application	Outdoor
Materials	Die-cast aluminum body with extruded aluminum pole, painted with epoxy powders, matt white color
Insulation class	Class I
Protection index	IP66
Impact degree	IK08
Ambient temperature (Ta)	'-25 / 45 °C
Optics	45° asymmetrical reflector in matt black painted steel sheet. Single-side lighting. Sanded extra-clear glass diffuser
Beam angle	45°
Power supply	220-240Vac
Frequency	50/60Hz
Led modules	Removable (Class: D)
Standard equipment	- 1000 mm long H05RN-F 3x1 mm ² neoprene cable. - Anti-condensation osmotic valve.
Luminous flux maintenance	L80-B50 > 75.000 h L80-B20 > 50.000 h
Wiring	Removable
Step Mac Adams	3 step
Photobiological safety class	Risk exempt group
Trademarks and certifications	CE / UNI EN 60598-1
Warranty	7 years

PRODUCT FEATURES

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
4.5	-	4000°K - CRI>80	1000 mm	409	91	60	60	1000	-	2.2



RELATED ACCESSORIES



ACC221

IP68 T-connector for through wiring. 5-pole connection.



ACC241

Universal dimmer with 230Vac phase cut output.

TEC-MAR
LIGHTING

TEC-MAR S.r.l. Via delle Industrie 1, 26835 Crespiatica (LO) – Italy

TEC-MAR S.r.l. reserves the right, without notice, to modify the characteristics of its products as well as their availability at any time. All products, related technical data, illustrations and information are not binding for TEC-MAR S.r.l. TEC-MAR S.r.l. will not be liable for any illustrative, textual and/or translation errors. All values reported are measurement values. Flow, CCT and power data are within tolerances of +/- 10%.

29-02-2024