
BOSTON/AM












SPECIFIC PRODUCT

Mod	AM							
Color	Matt white							
Installation	Led bollard							
Application	Outdoor							
Materials	Die-cast aluminum body with extruded aluminum pole, painted with epoxy powders, matt white color							
Insulation class	Class I							
Protection index	IP66							
Impact degree	IK08							
Ambient temperature (Ta)	'-25 / 45 °C							
Optics	45° asymmetrical reflector in matt black painted steel sheet. Single-side lighting. Sanded extra-clear glass diffuser							
Beam angle	45°							
Power supply	220-240Vac							
Frequency	50/60Hz							
Led modules	Removable (Class: D)							
Standard equipment	- 1000 mm long H05RN-F 3x1 mm² neoprene cable Anti-condensation osmotic valve.							
Luminous flux maintenance	L80-B50 > 75.000 h L80-B20 > 50.000 h							
Wiring	Removable							
Step Mac Adams	3 step							
Photobiological safety class	Risk exempt group							
Trademarks and certifications	CE / UNI EN 60598-1							
Warranty	7 years							

PRODUCT FEATURES

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
4.5	_	4000°K - CRI>80	250 mm	409	91	60	60	250	_	0.8



RELATED ACCESSORIES





ACC221 IP68 T-connector for through wiring. 5-pole connection.

ACC241 Universal dimmer with 230Vac phase cut output.



TEC-MAR S.r.I. Via delle Industrie 1, 26835 Crespiatica (LO) – Italy
TEC-MAR S.r.I. reserves the right, without notice, to modify the characteristics of its products as well as their availability at any time. All products, related technical data, illustrations and information are not binding for TEC-MAR S.r.I. TEC-MAR S.r.I. will not be liable for any illustrative, textual and/or translation errors. All values reported are measurement values. Flow, CCT and power data are within tolerances of +/- 10%.

29-02-2024