


**PALLA SUSPENSION UP ROUND 16** 16 alu pol/grey  
CPA05-0

**warmDIM**



**TECHNICAL SPECIFICATIONS**

|                                    |                            |
|------------------------------------|----------------------------|
| Lamp holder                        | LED                        |
| Mounting method                    | ceiling-mounted (surface)  |
| warmDIM                            | Yes                        |
| Light emission                     | direct                     |
| Light distribution                 | symmetric                  |
| Luminaire luminous flux            | 520 lm                     |
| Colour temperature                 | 2700-2200 K                |
| Colour rendering index (CRI)       | > 90                       |
| Rated voltage (range)              | 220-240 V / 120 V          |
| Power frequency                    | 50/60 Hz                   |
| Power consumption (maximum)        | 11 W                       |
| Surface                            | polished                   |
| Housing material                   | aluminium, opaline glass   |
| Type of lamp control gear          | Driver                     |
| Ballast included                   | Yes                        |
| Protection class                   | I                          |
| Connection cable (number of cores) | 3                          |
| Number of lampheads                | 1                          |
| Energy efficiency                  | A - A++                    |
| Dimmable                           | Yes                        |
| Type of Dimmer                     | Phase cutting (electronic) |
| Diameter                           | 160 mm                     |
| Head adjustable                    | No                         |
| Height adjustable                  | No                         |
| Suspension length                  | -/3000 mm                  |
| Custom length                      | Yes                        |

**tobias grau**