## U-LIGHT - AP ULI 090 - technical sheet





## APULI090

Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.

Available in several colours and sizes.


Typology: WALL LAMP

Ratings

- •Built in LED module
- •CCT 3000 K
- Uplight
- •Surface installation over holes
- •Supply voltage ~100-240VAC
- •Switch mode: on-off
- •Dimmable 1-10V LED driver
- •Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

Product code composition

example composition code



U-LIGHT / downlight or uplight mounting / DRIVER INCLUDED									
	Туре	Article	Colours	Code End	Source				
	AP	ULI 090 LED	AN anthracite grey	e XX		23W - diffused beam 8000K			
			RU rust brown						
	<b>C €</b>								

RU XX

AP ULI090LED

## Available colors





Anthracite grey

RU Rust brown

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER

ΔPIII	Inani	FD	XX

NOTES

Luminous flux (Im) and efficacy (Im/W) for all built-in LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.