

Andromeda 2211-01...30

Small chain suspension

Rev. 21/06/2023



Fitting for artistic lighting of pedestrian areas, gardens and park, with characteristic design and technical solutions in compliance with the latest norms. Body in die-cast aluminium ENAB43100, poles in extruded aluminium UNI EN 573-3, polyester powder anthracite color painted subject to anti-corrosion process. Anti-vandalic transparent or opal PMMA diffuser. Screws in A2 stainless steel. Sodium, metal halide or 23W-42W compact fluorescent lamp to suit all technical lighting requests. Lamellar shade anodized aluminium.

PLEASE NOTE:

This series supports the possibility of installing LED and IP67 sources which can be obtained by choosing one of our MODULED systems.

IMPORTANT:

The MODULED system can't be installed in the GLASS version.

FIXTURE SPECIFICATIONS

INSTALLATION

Ceiling installation

PROTECTION

IP 44

BODY

Pole: Extruded aluminium alloy -
Body/Base: Die-cast aluminium alloy

SCREEN

Transparent clear glass -
Optional: Frosted glass / Clear transparent PC / Opal PC

SEALS

Expanded silicone - moulded silicone

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

SIZES

H 980 x L 175 x W 175

MATERIAL

■ Aluminium



ELECTRICAL SPECIFICATIONS

POWER SUPPLY

220-240V

SOURCE

E27

OPTIK DISTRIBUTION


Lamp not included

ABSORBED POWER

75W Max

INSULATION CLASS

I



COLORS



00
PURE
WHITE RAL
9016

01
BLACK RAL
9005

10
WHITE RAL
9010

24
BRONZE

25
RUST

30
ANTHRACITE
SLATE
GREY

40
GREY RAL
9006

ACCESSORIES



MODULED-D

LED modules 15W-20W-30W - 3000K-4000K - IP67 adaptable to a selection of articles. For the complete list of electrifications and information download the MODULED-D file