

## Andromeda 2212-01...30

Medium chain suspension

Rev. 21/06/2023



Fitting for artistic lighting of pedestrian areas, gardens and park, with characteristic design and technical solutions in compliance with the latest norms. Body in die-cast aluminium ENAB43100, poles in extruded aluminium UNI EN 573-3, polyester powder anthracite color painted subject to anti-corrosion process. Anti-vandalic transparent or opal PMMA diffuser. Screws in A2 stainless steel. Sodium, metal halide or 23W-42W compact fluorescent lamp to suit all technical lighting requests. Lamellar shade anodized aluminium.

### PLEASE NOTE:

This series supports the possibility of installing LED and IP67 sources which can be obtained by choosing one of our MODULED systems.

### IMPORTANT:

The MODULED system can't be installed in the GLASS version.

## FIXTURE SPECIFICATIONS

### INSTALLATION

Ceiling installation

### PROTECTION

IP 44

### BODY

Pole: Extruded aluminium alloy -  
Body/Base: Die-cast aluminium alloy

### SCREEN

Transparent clear glass -  
Optional: Frosted glass / Clear transparent PC / Opal PC

### SEALS

Expanded silicone - moulded silicone

### SCREWS

Stainless steel A2

### PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

### SIZES

H 1030 x L 215 x W 215

### MATERIAL

■ Aluminium



MODU  
**LED**  
AVAILABLE

## ELECTRICAL SPECIFICATIONS

### POWER SUPPLY

220-240V

### SOURCE

E27

### OPTIK DISTRIBUTION


Lamp not included

### ABSORBED POWER

75W Max

### INSULATION CLASS

I



## COLORS



00  
PURE  
WHITE RAL  
9016

01  
BLACK RAL  
9005

10  
WHITE RAL  
9010

24  
BRONZE

25  
RUST

30  
ANTHRACITE SLATE  
GREY

35  
GREY RAL  
9006

## ACCESSORIES



**MODULED-D** LED modules 15W-20W-30W - 3000K-4000K - IP67 adaptable to a selection of articles. For the complete list of electrifications and information download the MODULED-D file