



# **PLSKR150**

## Design by Manuel Vivian


Collection of ceiling, suspended and table lamps in flameretardant TREVIRA®CS fabric (100% polyester Glow wire 960 °C), available in several sizes and colours. The fabric can also come in a double-layer version with an exterior black net fabric. A decorative inner lampshade (also printable with customized graphic) is available.

Typology: CEILING LAMP

# Ratings

- •E27
- Downlight
- ·Surface installation over holes
- •Supply voltage ~220-240V
- Switch mode: on-off
- ·Steel frame, painted
- •Cone in pongé fabric and light covering in jersey

Product code composition



#### SINGLE FABRIC

SINGLE FABRIC Fireproof class I= C1, GB= CRIB 5, D=B1, F= M1, EN= 102/1-2, A 652 / Weight 340 ± 5% gr/m² / Abrasion resistance (Martindale): 40.000 ± 10% rubs / Pilling Grade 5 / Light fastness grade 6

## BLACK NET FINISH FABRIC

Fireproof class I= C1, F= M1, D= B1 DIN 4102 / Weight 214 ± 5% gr/m² / Abrasion resistance (Martindale): 30.000 ± 10% rubs / Pilling Grade 5 / Light fastness grade 5

SKIRT / diffuser INCLUDED								
Туре	Article	Exterior Net		Fabric Colours		Source		
PL	SKR 150 E27	NE	black net	вс	white	E27	4 x Max 16W LED or 4 x Max 23W fluo or 4 x Max 70W halo	
	I	ХX	no black net	AR	orange		4 x Max 70VV Hato	
				ΑZ	light blue			
				BL	blue			
					fuchsia			
				ļ.	light grey			
					red			
					light green			
					, APP 0   3 COS			



PL SKR150E27 XX GR example composition code



RC. White



AR Orange



Light blue



RI Blue



FU Fuchsia



GR Light grey



MA Brown



RS Red



Light green



## Black net over a white fabric NEBC

EELc (Energy Efficiency Label compatibility): E, D, C, B, A, A+

CUSTOMER **NOTES** PLSKR150E27\_\_\_\_

# NOTICE:

Luminous flux (Im) and efficacy (Im/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.