

QUALITY MARKS



COLOURS




MIRA

Indoor recessed linear ceiling trim luminaire constructed of:

- Painted extruded aluminium structure available in two lengths: 1120 mm and 1680 mm
- Opal polycarbonate diffuser or UGR<19 lenses
- LED 3000K or 4000K CRI80 module
- ON-OFF or dimmable DALI integrated remote driver LED
- Spring fixing system (included)
- Painting using high resistance to UV and corrosion polyester powders

Code	Light source	Power	Lum. Flux *	Colour Temperature	Notes
7550.6OPX	LED CRI80	24W	2420 lm	4000 K	Opal diffuser
7550.6UGRX	LED CRI80	20W	3170 lm	4000 K	UGR<19 optic
7550.7OPX	LED CRI80	24W	2350 lm	3000 K	Opal diffuser
7550.7UGRX	LED CRI80	20W	2900 lm	3000 K	UGR<19 optic
7550D.6OPX	LED CRI80	24W	2420 lm	4000 K	Opal diffuser - DALI
7550D.6UGRX	LED CRI80	20W	3170 lm	4000 K	UGR<19 optic - DALI
7550D.7OPX	LED CRI80	24W	2350 lm	3000 K	Opal diffuser - DALI
7550D.7UGRX	LED CRI80	20W	2900 lm	3000 K	UGR<19 optic - DALI


* Lumen rating is related to the flux emitted by the LED module and not to the flux emitted by the appliance



Recessed ceiling version



Plasterboard cutting 38 mm x 1128 mm



LED:
The luminaire needs a remote power supplier (supplied)



On request