

#### QUALITY MARKS



There are no colors for the product.

## OCEAN SPOT

### Outdoor and indoor spotlight with adjustable optical group constructed of:







- Stainless steel AISI 316L body
- Stainless steel AISI 304 fixing bracket
- Tempered glass
- 10°, 45°, 90° optics
- Neoprene cable L 500 mm
- Silicon gaskets
- Stainless steel AISI 304 spike


## NOTES

Distance between driver and spotlight: max 20 mt  
Available with 10°, 45° optics

Code	Light source	Power	Lum. Flux *	Colour Temperature	Beam angle
4312.66.10X	LED CRI85	6W	730 lm	4000 K	10°
4312.66.45X	LED CRI85	6W	730 lm	4000 K	45°
4312.67.10X	LED CRI85	6W	670 lm	2700 K	10°
4312.67.45X	LED CRI85	6W	670 lm	2700 K	45°

\* Lumen rating is related to the flux emitted by the LED module and not to the flux emitted by the appliance

	Floor mounting		Operating temperature -40°C +50°C		Single power supply cables input		LED: The luminaire needs a remote power supply (supplied only on request)
	Impact Energy (J): 20		cod. A12:				

	<p>PQ 51: ACCESSORY (on request) Stainless steel AISI 304 ground spike.</p>
---	---