


# Rock\_W4



Wall Lights | 220-240 V | topLED 9.5 W 250 mA | CRI 80  
60735W00



Technical data	
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Power	9.5 W
Luminous flux (source)	1389 lm
Frequency	50 - 60 - Hz
CCT / Tonalità	3000 K
Colour rendering index	80 Ra
AC / DC	DC
Safety class	1
IP	IP55
IK	IK05
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Operating temperature	-40°C / +100°C
Driver included	Driver
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	2.9 Kg

Finishing casing	
Colour	grey

Finishing diffuser	
Material	Glass
Processing	Sandblasting

Wall Lights | 220-240 V | topLED 9.5 W 250 mA | CRI 80  
**60735W00**

Double emission wall lights for outdoor application. The warm white LED light source with a general lighting light distribution is composed of 52 topLEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 1389 lm, with a 146.2 lm/W nominal luminous efficacy.

The device body and features a grey finish; the diffuser is made of glass with a sandblasting treatment. The ingress protection degree is IP55; the total weight is of 2.9 kg.

The total absorbed power is 9.5 W.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Features	
Light Output Ratio (LOR)	47 %
Luminous flux (source)	1389 lm
Luminaire luminous flux	660 lm
Consumption	10 W
Luminaire efficacy	66 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra

UGR	
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 16
UGR axial	< 16

OPTICAL	
Light distribution simmetry	Symmetrical 2
Ottica C0/C180	103°
Ottica C90/C270	100°

