

2Nights_P6

Pendant Luminaires | 220-240 V | topLED 12 W 700 mA | CRI 90 8645



Technical data		
Designer	Davide Oppizz	
Installation position	Ceiling	
Installation environment	Indoor	
Light Source	LED	
Optics	Flood	
Light emission direction	downward	
Power	12 W	
Luminous flux (source)	1252 lm	
Frequency	60 - 50 Hz	
CCT / Tonalità	3000 K	
Colour rendering index	90 Ra	
Safety class	1	
IP	IP20	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	No	
Driver included	Yes	
Dimmable article	Phase cut	
Induzione	No	
Emergency mode	No	
Motion sensor	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	



• ب المحمد المحم

Finishing casin	9
Material	Aluminium
Colour	black RAL 9005
Processing	Coating
Finishing diffus	er
Material	PC
Colour	transparent
Finishing moun	ting frame
Material	Iron
Colour	black RAL 9005
Processing	Coating

2Nights_P6

Pendant Luminaires | 220-240 V | topLED 12 W 700 mA | CRI 90 8645

Single emission pendant luminaires for indoor application. The warm white LED light source with a flood light distribution is composed of 6 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 1252 lm, with a 104.3 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a black ral 9005 finish, processed by means of coating; the diffuser is made of PC; the mounting frame is made of iron, with a black ral 9005 finish, processed by means of coating. The ingress protection degree is IP20; The power supply driver is included in the delivery.

The total absorbed power is 12 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	1252 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra

2Nights_P6

