





Type	KOI10-11-8030-TD	<b>KOI10-11-8030-TD</b>
Order No	KOI10-11-8030-TD	
Lamp type/assembly	Standing light	
Colour	Chrome	
Colour temperature	3000 K	<b>MINERGIE®</b>
Colour rendering index	> 85	
Operating mode	Dimmable	
Operation	2 circuit push-button, integrated in stand	
Ballast (number)	LED Converter (2), integrated in luminaire head	
Lamp head	PC, aluminium metallised	
Diffuser	PC, prismatic, dyed white	
Tube	Steel, chrome-plated	
Base	X-shaped base; steel, aluminium-coloured, powder-coated	
Power cable	Black, 3x0.75mm <sup>2</sup> , L 5000 mm	
Mains plug	Swiss T12 (type J)	
Light distribution	Direct (27%) / indirect (73%)	
UGR	< 16	
Total luminous flux of luminaire	10688 lm @ 4000 K	
Power consumption	83 W	
Luminaire efficacy	128 lm/W @ 4000 K	
LED service life	55 000 h (L85)	
Mains voltage	220-240V, 50Hz	
Stand-by consumption	< 0.5 W	
Safety class	I	
Protection type	IP 20	
Packaging units	3 (ca. 600 x 600 x 230 + 2250 x 230 x 50 + 750 x 650 x 50 mm)	
Weight	20.7 kg	
Guarantee	36 months	



**Belux AG**  
 Neufeldweg 6, CH-5103 Möriken  
 Tel. +41 61 316 74 01  
 Fax +41 61 316 75 99  
 www.belux.com  
 belux@belux.com