

Job Name:

Ordering Code:

Fixture Type:

Bobo 1

BRUCK



Description

Bruck's European and American Artisan, mouth-blown glass is known throughout the world for its quality and beauty. Several light source options, mounting options, colors and finishes allow for a unique design. Most of Bruck's mini-pendant glass allows for easy screw-on / screw-off for a simple installation.

Standard cable length is 59". Overall cable length is measured and begins from uni-plug or top of mono-point. For the track adapters, overall cable length begins at the shoulder of the ECO/GEO adapter and the track center of the Zonyx adapter. Cable length measurement ends at the top of glass or to the mounting arms.

Ordering Codes

Follow the steps to specify your fixture,

example: (320 - 915 - mc - ecosv

Use Contract Contr	2 Shade Color	3 Finish	Mounting Option	
2231400 Im LED2212low voltage3203line voltage	909 clear 915 blue 917 red	bz bronze ch chrome mc matte chrome	MP 4" Canopy ecobk ECO/HALO black ecosv ECO/HALO matte silver ecowh ECO/HALO white geobk GEO black	
NOTES: 1. 223 for MP, UNI12 and M 2. 221 for MP and UNI12 m 3. 320 for MP, eco, geo, an	geosy GEO matte silver geowh GEO white zonmc Zonyx matte chrome UNI12 Uni-Plug 12 MULTI LED multi-point			

	Job Name:		Contact:			
	Ordering Code:		Fixture Type:	Fixture Type:		
$ \underbrace{\left[\begin{array}{c} 1 \\ 1 \\ 4 \end{array} \right]}_{4^{''}} \underbrace{\left[\begin{array}{c} 1 \\ 2 \\ 2 \\ 3 \\ 2 \\ 3 \\ 2 \\ 2 \\ 3 \\ 2 \\ 2$						
Light Source	223 - LED	221 - Iow voltage (Bi-Pin)	320 - line voltage G9			
Performance		1				
LED LUMEN CCT SDCM CRI LIFE	Cree XTE 400 Im 2800k 3 MacAdam Elipse, +/-75 Kelvin 90 min. based on IESNA-LM80-2008: 90% of initial lumens after 60,500 hrs	lamp dependent	Iamp dependent			
Technical Specs						
Socket Listing	integrated LED module ETLus Listed to UL1598, UL1574 and UL2108 (Suitable for dry locations only) cETL Listed to CSA C22.2 #250.0 and #9.0	GY6.35 socket ETLus Listed to UL1598, UL1574 and UL2108 (Suitable for dry locations only) cETL Listed to CSA C22.2 #250.0 and #9.0	G9 socket ETLus Listed to UL1598, UL1574 and UL2108 (Suitable for dry locations only) CETL Listed to CSA C22.2 #250.0 and #9.0			
Mounting						
Uni-Plug UNI12	 12V AC input 9W, 11.3VA Dimmable 	 12V AC/DC input 50W, 50VA (max 50W lamp) Dimmable Connects to Uni-Light system with appropriate low voltage adapter (V/A, Enzis, High-Line) or line voltage adapter (ECO, GEO, Zonyx) 				
4" Canopy	 120-277 50/60Hz input 8W, 8VA Dimmable: ELV (Reverse Phase) Mount to 3 1/2" - 4" round J-Box Short circuit protection Thermal protection 	 120VAC 50/60Hz input 11.7V AC output 49W, 50VA (max 50W lamp) Dimmable (Trailing Edge ELV) Mount to 3 1/2" - 4" round J-Box Short circuit protection Overload protection Thermal protection 	 120VAC 50/60 Hz input 40W, 40VA (max 40W lamp) Dimmable (incandescent) Mount to 3" - 4" round J-Box 			
Line Voltage Track			 120VAC 50/60 Hz input 40W, 40VA (max 40W lamp) Dimmable (Incandescent) Connects to ECO, GEO, or Zonyx system 			
MULTI	 700mA constant current input 6.3W Mounts to low voltage LED multi-point canopy Dimmable, refer to low voltage LED canopy spec sheet 					
Warranty						

• 5 year limited fixture warranty



Made in the USA - meets the requirements of the Buy American provision within the ARRA

• 1 year limited fixture warranty

• 1 year limited fixture warranty