

Products /  NORLIGHT / BUBBLE / BUBBLE 1000 / DD15SC102AE

## BUBBLE DD15SC102AE

### TECHNICAL DATA

#### GENERAL



Item code	DD15SC102AE
Place installation	indoor
Name	BUBBLE 1000 / DD15SC102AE ceiling, suspension
Standard colour	AE - white RAL 9003
Variant colour	CH - semi-bright aluminium RAL 9006
Environments	hallway, conference hall, art and culture, leisure areas, retail areas, places of worship
Designer	ALFONSO FEMIA /AF*design




#### PHYSICAL

Installation type	ceiling, suspension
Mounting type	surface
Body	Round metal frame, seats for the electrical components and anchor points for the suspension device and diffusers.
Glow wire resistance	850°C



#### DIMENSIONS

H: Total height device (mm)	240
D: Total diameter device (mm)	1000
Weight (kg)	16,1




#### OPTICAL SYSTEMS

Emission	diffuse
Optical System	Smooth opal polycarbonate diffuser, injection moulded, shock-resistant, anti-ageing.

## ENERGY SAVING

This luminaire contains built-in LED lamps  
The lamps cannot be changed in the luminaire




## SOURCES

Source Type	Source Power	System Power	Source	Lamp Socket	Sources Temperature	Colour	Nominal Flux	Output Flux	Source description
LED RGB	-	115W	-	-	-	-	-	3456 lm	-

## ELECTRICAL

Ballast type	Digital MultipleX
Mounting ballast type	Remote
Voltage	24V-DC
Wiring	Electrical harness wired for 24V-DC. DMX interface. Terminal block, DMX+, DMX-, till 2.5mm <sup>2</sup> DMX. Remote power supply of 220-240V-AC 50-60Hz (to be ordered separately).

## PHOTOMETRICS



Total return LOR 100,00 %

## NORMS / DIRECTIVES

Norms	EN 60598-1, EN 60598-2-1
Directives	2014/35/UE, 2014/30/UE

## ACCESSORIES

### INCLUDED ACCESSORIES

#### Electrical

Power cable L=10000mm

LED sources RGB

#### Mounting

Ceiling rose in Ø220mm (monolithic ceilings and modular false ceilings)

Cylindrical ceiling rose for installation into load bearing ceilings (max 35 kg)

Suspension kit with steel cables L=10000mm

## OPTIONAL ACCESSORIES

### Electrical

Accessory code	D64/D100-01
Technical description	Extraction key + Electronic power supply designed to mount on a DIN standard profile IP20 120W - Vin=100~264V-AC 47~63Hz Vout=24V.
A: Total width device (mm)	125



Accessory code	MEC6137
Technical description	Pro Touch DMX512 programmable controller with outer 5-12V-AC/DC adapter.

Accessory code	MEC6136
Technical description	Easy Touch DMX512 controller with outer 9-24V-AC/DC adapter.