

Products /  NORLIGHT / BUBBLE / BUBBLE 1800 / DD15SC103AE

BUBBLE DD15SC103AE

TECHNICAL DATA

GENERAL



Item code	DD15SC103AE
Place installation	indoor
Name	BUBBLE 1800 / DD15SC103AE ceiling, suspension
Standard colour	AE - white RAL 9003
Variant colour	CH - semi-bright aluminium RAL 9006
Environments	hallway, conference hall, art and culture, leisure areas, retail areas, places of worship
Designer	ALFONSO FEMIA /AF*design




PHYSICAL

Installation type	ceiling, suspension
Mounting type	surface
Body	Round metal frame, seats for the electrical components and anchor points for the suspension device and diffusers.
Glow wire resistance	850°C



DIMENSIONS

H: Total height device (mm)	240
D: Total diameter device (mm)	1800
Weight (kg)	33



OPTICAL SYSTEMS

Emission	diffuse
Optical System	Smooth opal polycarbonate diffuser, injection moulded, shock-resistant, anti-ageing.

ENERGY SAVING

This luminaire contains built-in LED lamps
The lamps cannot be changed in the luminaire



SOURCES

Source Type	Source Power	System Power	Source	Lamp Socket	Sources Temperature Colour	Nominal Flux	Output Flux	Source description
LED RGB	-	225W	-	-	-	-	6912 lm	-

ELECTRICAL

Ballast type	Digital MultipleX
Mounting ballast type	Remote
Voltage	24V-DC
Wiring	Electrical harness wired for 24V-DC. DMX interface. Terminal block, DMX+, DMX-, till 2.5mm ² DMX. Remote power supply of 220-240V-AC 50-60Hz (to be ordered separately).

PHOTOMETRICS

Total return LOR	100,00 %
------------------	----------

NORMS / DIRECTIVES

Norms	EN 60598-1, EN 60598-2-1
Directives	2014/35/UE, 2014/30/UE

ACCESSORIES

INCLUDED ACCESSORIES

Electrical

Power cable L=10000mm

LED sources RGB

Mounting

Ceiling rose in Ø220mm (monolithic ceilings and modular false ceilings)

Cylindrical ceiling rose for installation into load bearing ceilings (max 35 kg)

Suspension kit with steel cables L=10000mm

OPTIONAL ACCESSORIES

Electrical

Accessory code	D64/D300-01
Technical description	Extraction key + Electronic power supply designed to mount on a DIN standard profile IP20 240W - Vin=100~264V-AC 47~63Hz Vout=24V.
A: Total width device (mm)	125



Accessory code	MEC6137
Technical description	Pro Touch DMX512 programmable controller with outer 5-12V-AC/DC adapter.

Accessory code	MEC6136
Technical description	Easy Touch DMX512 controller with outer 9-24V-AC/DC adapter.