

Products /  NORLIGHT / BUBBLE / BUBBLE 3000 SUSPENDED PARALLEL CABLES WITHOUT JOINT / DD15SC604AE

BUBBLE DD15SC604AE

TECHNICAL DATA

GENERAL



Item code	DD15SC604AE
Place installation	indoor
Name	BUBBLE 3000 SUSPENDED PARALLEL CABLES WITHOUT JOINT / DD15SC604AE suspension
Standard colour	AE - white RAL 9003
Variant colour	CH - semi-bright aluminium RAL 9006
Environments	hallway, conference hall, art and culture, leisure areas, retail areas, places of worship
Designer	ALFONSO FEMIA /AF*design




PHYSICAL

Installation type	suspension
Mounting type	surface
Body	Round metal frame, seats for the electrical components and anchor points for the suspension device and diffusers.
Glow wire resistance	850°C



DIMENSIONS

H: Total height device (mm)	240
D: Total diameter device (mm)	2800
Weight (kg)	57




OPTICAL SYSTEMS

Emission	diffuse
Optical System	Smooth opal polycarbonate diffuser, injection moulded, shock-resistant, anti-ageing.

ENERGY SAVING

This luminaire contains built-in LED lamps
The lamps cannot be changed in the luminaire



SOURCES

Source Type	Source Power	System Power	Source	Lamp Socket	Sources Temperature	Colour	Nominal Flux	Output Flux	Source description
LED RGB	-	338W	-	-	-	-	-	10400 lm	-

ELECTRICAL

Ballast type	Digital MultipleX
Mounting ballast type	Remote
Voltage	24V-DC
Wiring	Electrical harness wired for 24V-DC. DMX interface. Terminal block, DMX+, DMX-, till 2.5mm ² DMX. Remote power supply of 220-240V-AC 50-60Hz (to be ordered separately).

PHOTOMETRICS

Total return LOR	100,00 %
------------------	----------

NORMS / DIRECTIVES

Norms	EN 60598-1, EN 60598-2-1
Directives	2014/35/UE, 2014/30/UE

ACCESSORIES

INCLUDED ACCESSORIES

Electrical

Power cable L=2000mm

LED sources RGB

Mounting

Ceiling rose in Ø220mm (monolithic ceilings and modular false ceilings)

Suspension kit complete with 8 steel cables L=2000mm and small ceiling roses

Transparent ceiling rose with terminal device

OPTIONAL ACCESSORIES

Electrical

Accessory code	MEC6137
Technical description	Pro Touch DMX512 programmable controller with outer 5-12V-AC/DC adapter.
Accessory code	MEC6136
Technical description	Easy Touch DMX512 controller with outer 9-24V-AC/DC adapter.
Accessory code	MEC6357
Technical description	Electronic power supply designed to mount on a DIN standard profile 480W - Vin=100~264V-AC 47~63Hz Vout=24V.
A: Total width device (mm)	125

