

Products /  NORLIGHT / BUBBLE / BUBBLE 600 / DD15SL101AE

BUBBLE DD15SL101AE

TECHNICAL DATA

GENERAL



| | |
|--------------------|---|
| Item code | DD15SL101AE |
| Place installation | indoor |
| Name | BUBBLE 600 / DD15SL101AE ceiling, suspension |
| Standard colour | AE - white RAL 9003 |
| Variant colour | CH - semi-bright aluminium RAL 9006 |
| Environments | hallway, conference hall, art and culture, leisure areas, retail areas, places of worship |
| Designer | ALFONSO FEMIA /AF*design |




PHYSICAL

| | |
|----------------------|---|
| Installation type | ceiling, suspension |
| Mounting type | surface |
| Body | Round metal frame, seats for the electrical components and anchor points for the suspension device and diffusers. |
| Glow wire resistance | 850°C |



DIMENSIONS

| | |
|-------------------------------|-----|
| H: Total height device (mm) | 190 |
| D: Total diameter device (mm) | 600 |
| Weight (kg) | 8,1 |




OPTICAL SYSTEMS

| | |
|----------------|--|
| Emission | diffuse |
| Optical System | Smooth opal polycarbonate diffuser, injection moulded, shock-resistant, anti-ageing. |

ENERGY SAVING

This luminaire contains built-in LED lamps
The lamps cannot be changed in the luminaire




SOURCES

| Source Type | Source Power | System Power | Source | Lamp Socket | Sources Temperature | Colour | Nominal Flux | Output Flux | Source description |
|-------------|--------------|--------------|--------------|-------------|---------------------|--------|--------------|-------------|--------------------|
| LED | - | 55W | 6 LED engine | - | 3000K | - | - | 2510 lm | - |

ELECTRICAL

| | |
|-----------------------|---|
| Ballast type | Electronic with dimmer DALI |
| Mounting ballast type | Integral |
| Voltage | 220-240V |
| Frequency | 50-60Hz |
| Wiring | Electrical harness wired for 220-240V-AC 50-60Hz power supply. 2.5mm ² LTN terminal block. DALI dimmable electronic ballast. |

PHOTOMETRICS



NORMS / DIRECTIVES

| | |
|------------|--------------------------|
| Norms | EN 60598-1, EN 60598-2-1 |
| Directives | 2014/35/UE, 2014/30/UE |

ACCESSORIES

INCLUDED ACCESSORIES

Electrical

Power cable L=10000mm

LED sources 3000K

Mounting

Suspension kit with steel cables L=10000mm

Ceiling rose in Ø220mm (monolithic ceilings and modular false ceilings)

Cylindrical ceiling rose for installation into load bearing ceilings (max 35 kg)

OPTIONAL ACCESSORIES

Electrical

Accessory code **MEC6134**

Technical description
Dimming DALI Kit (Wireless receivers unit + portable hand transmitter).

Accessory code **MEC6135**

Technical description
Dimming DALI Kit (Wireless receivers unit + portable table/wall transmitter with integrated light sensor).

Accessory code **MEC6161**

Technical description
Dimming DALI Kit (Remote Controller via push-button for multi luminaires installation).


Mounting

Accessory code **MEC6141**

Technical description
BUBBLE 600/1000 - Replacement suspension kit L=25000mm for great heights (3 steel cable + 5 poles power supply cable).

Accessory code **150A034AE**

Technical description
BUBBLE 600/1000 - Connection joint for suspension mounting on horizontal cables.



Accessory code **MEC6129**

Technical description
BUBBLE ArcoLED 600/1000 - Suspension mounting kit for load bearing false-ceilings, including spacers, 3 steel cables in L=2000mm and a millimetric adjuster, 3 conical ceiling roses.