FRAMEWORK LED - PL FW MXXX - technical sheet



	Collection suspende Available also supp light sour	80 70 y Manuel Vivian n consisting of ceiling or v ed lamps in white aluminiu in several sizes. The ceil vlied in three different heig	im. and floor lamps. ing/wall lamps are	Ratings •Built in Demodule •CCT 3000 K •Uplight •Surface installation over holes •Supply voltage ~220-240V •Switch mode: on-off •Dimmable DALI LED driver •Extruded aluminium profile, painted •Linear prismatic diffuser
	Product c	ode composition		
	FRAM	EWORK / DRIVER INCLUDE	D / applicazione a soffit	to o a parete / application: both as ceiling or wall lamp
PL FW M 090 kg 9,2 m³ 0.37 PL FW M 180 kg 9,3 m³ 0.37	Туре	Article Colour	s Code En	d Source
PL FW M 270 kg 9,4 m ³ 0.37	PL	FW M 090 LED BC wh	nite XX	LED 70W - diffused beam 3000K*, 4000K
*	or 22.3 cm or 31.3 cm	FW M 180 LED		
mains		FW M 270 LED		
5 cm 127 cm	CE	IP20 CRI80	1 LED ~9920 lm	
Available colors BC Wrinkled white aluminium				
EELc (Energy Efficiency Label compatibilit	y) contain built	in LED lamps that cannot	be changed: A, A+, A	Δ++
CUST PLFWMLED BCXX	CUSTOMER		:S	
NOTICE: Luminous flux (Im) and efficacy (Im/W) for all LED lu Technical data could be subject to alteration without	minaires is based o notice. Axo Light c	on nominal ratings of the LED s loes not provide legal guarante	ources. e for the accuracy of this c	lata sheet.

AXO LIGHT srl, via Moglianese 44 - 30037 Scorzè (VE), Italy - T +39 041 5845193 - F +39 041 5845060 axolight@axolight.it - www.axolight.it