



PLMUSE60

Design by Sandro Santantonio

Collection consisting of ceiling or wall lamps, suspended lamps and table lamps with metal frame and removable, washable elastic fabric covering. Available in several colours and sizes. Screw fitting light source.

Typology: WALL, CEILING


Ratings

- •E27
- •Diffused light
- Surface installation over holes
- •Supply voltage ~220-240V
- •Switch mode: on-off
- ·Steel frame, painted

Product code composition

kg 1.5 m³ 0.09





Ø 60 cm

Silk stretch fabric

Comp. 84% polyester, 16% elastane (Spandex) for multicolour MC. Comp. 80% polyamide, 20% elastane (Spandex) for other colours.

Weight 170/190 gr/m² for multicolour MC. Weight 195/215 gr/m² for white BC Weight 180/200 gr/m² for other colours.

Light fastness (ISO 105 B02) from 3 to 6 Glow wire 750°C for multicolour MC Glow wire 850°C for white BC / other colours.

MUSE / tessuto INCLUSO, kit lente NON PREVISTO / fabric INCLUDED, glass diffuser kit NOT AVAILABLE / applicazione a soffitto o a parete / application; both as ceiling or wall lamp

Type Article		ours	Finish
Pa cicio	osiou. s		
PL MUSE 60	ВС	white	XX white
	AR	orange	
	ΑZ	light blue	
	BL	dark blue	
	FU	fuchsia	
	GI	yellow	
	RO	pink	
	RS	red	
	VE	green	
	VI	violet	
	мС	multicolour	
	Fl	flower	
	ST	sticks	
	Article MUSE 60	MUSE 60 BC AR AZ BL FU GI RO RS VE VI MC FI	

Source

2 x Max 6,5W LED or 2 x Max 42W halo

(€ (≟) IP20 +LED 220-240VAC

example composition code

for optional accessories please refer to our pricelist or contact our representatives

PL MUSE60 ST XX E27



EELc (Energy Efficiency Label compatibility): E, D, C, B, A, A+, A++

CUSTOMER **NOTES** PLMUSE60_ _XXE27

Luminous flux (Im) and efficacy (Im/W) for all built-in LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.