### Beacon LED Muse II BEACON LED MUSE II 97CRI 3000K L3 ON-BOARD DIM WHITE 2059745



#### Product features

Integrated LED spotlight, white RAL 9016, unique soft-touch ring, adjustable beam angle from a 8° spot to a 55° flood, compact and minimalist design, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 8° spot to 55° flood, optics: aspheric glass lens, colour temperature: 3000K warm white, total system power: 21W, total fixture output: 1081lm, luminaire efficacy: 51lm/W, LOR: 100%, colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, lifetime: >72,000 hours at L80B10, energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x135x176mm, weight: 0.95kg.



#### PRODUCT OVERVIEW

IPC Code	2059745
Product name	BEACON LED MUSE II 97CRI 3000K L3 ON-BOARD DIM WHITE
Technology	LED
Housing	Aluminium
Mount	Track mounting
General application	Museums & Galleries
Certifications	EUNEW009
ETIM Class	EC001744
E-number FI	4280893
Fixture luminous flux (Im)	553/1081
Luminaire efficacy (Im/W)	52
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	97
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	21
Product Voltage (V)	240
Electrical protection	Class II
Dimmable	Yes
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Product EAN number	5025768597451
Lamps	Yes
Included lamp	INTEGRATED LED

#### DATA TABLE


### Beacon LED Muse II BEACON LED MUSE II 97CRI 3000K L3 ON-BOARD DIM WHITE 2059745

General data	
IPC Code	2059745
Product name	BEACON LED MUSE II 97CRI 3000K L3 ON-BOARD DIM WHITE
Technology	LED
Housing	Aluminium
Mount	Track mounting
General application	Museums & Galleries
Operating temperature rated (°C)	25
Certifications	EUNEW009
ETIM Class	EC001744
E-number FI	4280893
Optical data	
Fixture luminous flux (Im)	553/1081
Luminaire efficacy (Im/W)	52
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	97
Colour Variation Initial (SDCM)	3
Electrical data	
Total power consumption (W)	21
Mains voltage (V)	230-240V~
Product Voltage (V)	240
Electrical protection	Class II
Dimmable	Yes
Drive current (mA)	500
Inrush Current (A)	45
Inrush Duration (μs)	20
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 16A C Breaker	80
Lifetime data	70000
Lumen maintenance - L70 B50	72000
Physical data	
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Nominal Product Width (mm)	135
Nominal Product Height (mm)	176
Nominal Product Diameter (mm)	80
Weight (kg)	1.01

### Beacon LED Muse II BEACON LED MUSE II 97CRI 3000K L3 ON-BOARD DIM WHITE 2059745


Packaging	
Single packaging type	Carton
Product EAN number	5025768597451
Packaging single length / height (cm)	17.5
Packaging single width (cm)	15.0
Packaging single depth (cm)	17.5
DUN14 (outer)	05025768597451
Units per outer package	1
Packaging outer length / height (cm)	17.5
Packaging outer width (cm)	15.0
Packaging outer depth (cm)	17.5
Safety data	
Dry applications use only	Yes

#### PHOTOMETRY



#### TECHNICAL DRAWINGS

### Beacon LED Muse II BEACON LED MUSE II 97CRI 3000K L3 ON-BOARD DIM WHITE 2059745



### Beacon LED Muse II BEACON LED MUSE II 97CRI 3000K L3 ON-BOARD DIM WHITE 2059745

