

Job Name:

Contact:

Ordering Code:

Fixture Type:

Houston Sconce



Description
The Houston collection is handcrafted by Murano glass masters featuring a contemporary square shape. The vivid colors offered include red, orange, vanilla and white. It is offered in matte chrome, chrome or bronze. ADA compliant.

Ordering Codes
Follow the steps to specify your fixture,

example:

| ① | Light Source | ② | Shade Color | ③ | Finish |
|---|--|--|-------------|--|--------|
| | 100 low voltage canopy 104 LED canopy | 850 white 851 vanilla 852 red | | bz bronze ch chrome mc matte chrome | |




Job Name:

Contact:

Ordering Code:

Fixture Type:



Light Source 104 - 150 lm LED 100 - low voltage

| Performance | | | |
|-----------------|---|---|--|
| LED | • Nichia 219B | • lamp dependent | |
| CCT | • 3000k | | |
| CRI | • DUV: +/- .002 | | |
| LIFE | • 83 typ | | |
| | • based on IESNA-LM80-2008: 70% of initial lumens after 60,300 hrs | | |
| Technical Specs | | | |
| Socket Listing | • integrated LED module | • GY6.35 socket | |
| | • ETLus Listed to UL1598, UL1574 and UL2108 (Suitable for dry locations only) | • ETLus Listed to UL1598, UL1574 and UL2108 (Suitable for dry locations only) | |
| | • cETL Listed to CSA C22.2 #250.0 and #9.0 | • cETL Listed to CSA C22.2 #250.0 and #9.0 | |
| Mounting | | | |
| Canopy | • 100-277VAC, 50/60Hz input | • 120VAC 50/60Hz input | |
| | • 4W, 7.5VA | • 11.7V AC output 49W, 50VA (max 50W lamp) | |
| | • Mount to 3 1/2" - 4" round J-Box | • Mount to 3 1/2" - 4" round J-Box | |
| | • Short circuit protection | • Short circuit protection | |
| | • Thermal protection | • Overload protection | |
| | | • Thermal protection | |
| Warranty | | | |
| | • 3 year limited fixture warranty | • 1 year limited fixture warranty | |



Made in the USA - meets the requirements of the Buy American provision within the ARRA